This document provides pertinent information concerning the reissuance of the VPDES Permit listed below. This permit is being processed as a minor, municipal permit. The discharge results from the operation of a 0.0063 MGD wastewater treatment plant and includes an expansion flow tier of 0.01175 MGD. This permit action consists of updating the proposed effluent limits to reflect the current Virginia WQS (effective January 6, 2011) and updating permit language as appropriate. The effluent limitations and special conditions contained within this permit will maintain the Water Quality Standards of 9VAC25-260 et seq.

1.	Facility Name and Mailing Address:	Lucketts Elementary School 21000 Education Court Ashburn, VA 20148	SIC Code:	4952 WWTP 8211 Elementary School
	Facility Location:	14550 James Monroe Highway Leesburg, VA 20176	County:	Loudoun
	Facility Contact Name:	William Kolster	Telephone Number:	571-252-2960
	Facility Email Address:	William.Kolster@lcps.org		
2.	Permit No.:	VA0021750	Expiration Date:	5 January 2014
	Other VPDES Permits:	Not Applicable		
	Other Permits:	Registration ID 3008369 – Undergro	und Petroleum Storage Tank	(UST)
	E2/E3/E4 Status:	Not Applicable		
3.	Owner Name:	Loudoun County Public Schools		
	Owner Contact / Title:	William Kolster Director of Facilities Services	Telephone Number:	571-252-2960
	Owner Email Address:	William.Kolster@lcps.org		
4.	Application Complete Date:	23 May 2013		
	Permit Drafted By:	Douglas Frasier	Date Drafted:	13 June 2013
	Draft Permit Reviewed By:	Alison Thompson	Date Reviewed:	26 June 2013
	WPM Review By:	Bryant Thomas	Date Reviewed:	28 June 2013
	Public Comment Period:	Start Date: 18 July 2013	End Date:	16 August 2013
5.	Receiving Waters Information:	See Attachment 1 for the Flow Frequ	uency Determination.	
	Receiving Stream Name:	Limestone Branch, UT	Stream Code:	laXAQ
	Drainage Area at Outfall:	0.14 square miles	River Mile:	3.69
	Stream Basin:	Potomac River	Subbasin:	Potomac River
	Section:	8	Stream Class:	III
	Special Standards:	PWS	Waterbody ID:	VAN-A03R
	7Q10 Low Flow:	0.0MGD	7Q10 High Flow:	0.0 MGD
	1Q10 Low Flow:	0.0 MGD	1Q10 High Flow:	0.0 MGD
	30Q10 Low Flow:	0.0 MGD	30Q10 High Flow:	0.0 MGD
	Harmonic Mean Flow:	0.0 MGD	30Q5 Flow:	0.0 MGD
6.	Statutory or Regulatory Basis for	or Special Conditions and Effluent Limit	tations:	
	State Water Control Lav	W	EPA Guidelines	
	✓ Clean Water Act		✓ Water Quality Sta	ndards
	✓ VPDES Permit Regulati	ion	Other	
	✓ EPA NPDES Regulation	n	 -	
7.	Licensed Operator Requirement	s: Class IV		

8.

Reliability Class:

Class II

VPDES PERMIT PROGRAM FACT SHEET

VA0021750 PAGE 2 of 10

^	300		~11			•		
9.	Peri		ı n	ara	rtei	P170	ITIN'	n۰
7.	1 (1)	1111	~11	arat		12.0	ILIU.	

•	Private	✓	Effluent Limited	✓	Possible Interstate Effect
	Federal	✓	Water Quality Limited		Compliance Schedule Required
	State		Toxics Monitoring Program Required		Interim Limits in Permit
✓	POTW		Pretreatment Program Required		Interim Limits in Other Document
✓	TMDL				

10. Wastewater Sources and Treatment Description:

The Lucketts Elementary School wastewater treatment plant (WWTP) serves an elementary school, consisting of approximately 300 students and staff, the Lucketts Community Center (includes a day care of approximately 60 children) and the Lucketts Volunteer Fire Station. Treatment consists of a grease trap, septic tank, dosing tank, sand filter bed, chlorine disinfection and dechlorination.

See Attachment 2 for a facility schematic/diagram.

		*e@a: TABLI OUTFALL DES	E I _C SERIPTION	
Number	Discharge Sources	Treatment	Design Flow(s)	/Lainude/Asonglide/
001	Domestic Wastewater	See Section 10 above	0.0063 MGD 0.01175 MGD (expansion)	39° 12' 47" / 77° 31' 56"
See Atta	chment 3 for the Waterford	topographic map.		

11. Sludge Treatment and Disposal Methods:

Domestic sludge is not generated on site. Septic tanks are pumped routinely by a licensed contract hauler and taken to an approved Loudoun Water facility for disposal and treatment.

12. Discharges and Intakes Located Within the Vicinity of Discharge:

	TABLE 2 DISCHARGES AND INT	AKESA	
Permit Number	Facility Name F	a Vicye Týpe	Receiving Stream
VA0092380	Elysian Heights Sewage Treatment Plant		Potomac River
VA0061280	Skills USA/VICA Wastewater Treatment Plant]	Clarks Run
VA0074934	One Stop Trailer Park		Clarks Run
VA0074942	Hiway Mobile Home Community	Municipal Discharge Individual Permit	Limestone Branch, UT
VA0067938			Limestone Branch, UT
VA0088196			Limestone Branch
VA0092282	Leesburg Water Pollution Control Facility		Potomac River
VA0090573	Beacon Hill Water Treatment Plant	Industrial Discharge Individual Permit	Limestone Branch, UT
PWSID 6107300	Town of Leesburg (upstream of discharge)	raw water intake	·
PWSID 6059501	Fairfax Water (downstream of discharge)	Potomac River	

13. Material Storage:

	TABLE 3 MATERIAL STORAGE	
Materials Description	Volume Stored	Spill/Stormwater Prevention Measures.
Hypochlorite solution	5 cases	Constitute to the state of the
Dechlorination tablets	1 5-gallon bucket	Stored inside locked control building

14. Site Inspection: Performed by NRO Compliance Staff on 12 February 2009. See Attachment 4 for the inspection summary.

15. Receiving Stream Water Quality and Water Quality Standards:

a. Ambient Water Quality Data

The facility discharges to a segment of the unnamed tributary to Limestone Branch (1aXAQ) that has not been monitored or assessed by DEQ. However, there is a DEQ monitoring station on the unnamed tributary to Limestone Branch located approximately 2.8 miles downstream of Outfall 001. Monitoring station 1aXAQ000.85 is located at the Rt. 661 bridge crossing. The following is the water quality summary for the downstream portion of the unnamed tributary, as taken from the Draft 2012 Integrated Report*:

The following are the DEQ ambient monitoring stations located on the unnamed tributary to Limestone Branch: 1aXAQ000.85, at Route 661.

E. coli monitoring finds a bacteria impairment, resulting in an impaired classification for the recreation use. This impairment is nested within the downstream completed bacteria TMDL for Limestone Branch.

The aquatic life use is fully supporting; however, an observed effect for the aquatic life use is noted as citizen monitoring finds a medium probability of adverse conditions for biota.

The wildlife use is considered fully supporting.

The fish consumption and public water supply uses were not assessed.

b. 303(d) Listed Stream Segments and Total Maximum Daily Loads (TMDLs)

Waterbody Name	INFORI Impaired Use		Distance	TABLE 4 STREAM 303(d) IMPAIRMEN TMDL completed	WEA	
	Impairment Information in the Draft 2012 Integrated Report*					
Unnamed Tributary to Limestone Branch	Recreation	E. coli	1.7 miles	Limestone Branch Bacteria 7/6/2004 modified 9/24/08 & 3/10/10	2.05E+10 cfu/year E. coli	126 cfu/100mL <i>E. coli</i> 0.01175 MGD

Virginia's Draft 2012 Integrated Report (IR) has been through the public comment period and reviewed by EPA.

The 2012 IR is currently awaiting final approval.

The full planning statement is found in Attachment 5.

^{*}Virginia's Draft 2012 Integrated Report (IR) has been through the public comment period and reviewed by EPA. The 2012 IR is currently awaiting final approval.

c. Receiving Stream Water Quality Criteria

Part IX of 9VAC25-260(360-550) designates classes and special standards applicable to defined Virginia river basins and sections. The receiving stream, Limestone Branch, UT, is located within Section 8 of the Potomac River Basin and classified as Class III water.

At all times, Class III waters must achieve a dissolved oxygen (D.O.) of 4.0 mg/L or greater, a daily average D.O. of 5.0 mg/L or greater, a temperature that does not exceed 32° C and maintain a pH of 6.0 - 9.0 standard units (S.U.).

Attachments 6 and 7 detail other water quality criteria applicable to the receiving stream for the 0.0063 MGD facility and the 0.01175 MGD expansion, respectively.

Ammonia:

The fresh water, aquatic life Water Quality Criteria for ammonia is dependent on the instream pH and temperature. The 90th percentile pH and temperature values are used because they best represent the critical conditions of the receiving stream. The 30Q10 and 1Q10 of the receiving stream are 0.0 MGD. In cases such as this, effluent pH and temperature data may be used to establish the ammonia water quality standard. See **Attachment 8** for effluent pH data. Since effluent temperature data is not readily available, a default value of 25° C for summer and an assumed 15° C for winter will be utilized.

Metals Criteria:

The Water Quality Criteria for some metals are dependent on the receiving stream and/or the effluent hardness values (expressed as mg/L calcium carbonate). Since the 7Q10 of the receiving stream is zero and there is no ambient data available, agency guidance states that the effluent hardness may be utilized. The previous reissuance used a value of 150 mg/L CaCO₃, obtained from effluent sampling, to ascertain the criteria. Given the source and lack of variability in the waste stream, it is staff's best professional judgement to utilize the aforementioned value for this reissuance.

The hardness-dependent metals criteria shown in Attachments 6 and 7 are based on this value.

Bacteria Criteria:

The Virginia Water Quality Standards at 9VAC25-260-170.A state that the following criteria shall apply to protect primary recreational uses in surface waters:

E. coli bacteria per 100 mL of water shall not exceed a monthly geometric mean of the following:

·	 Geometric Mean ¹
Freshwater E. coli (N/100 mL)	126

¹For a minimum of four weekly samples taken during any calendar month.

d. Receiving Stream Special Standards

The State Water Control Board's Water Quality Standards, River Basin Section Tables (9VAC25-260-360, 370 and 380) designates the river basins, sections, classes and special standards for surface waters of the Commonwealth of Virginia. The receiving stream, Limestone Branch, UT, is located within Section 8 of the Potomac River Basin. This section has been designated with a special standard of 'PWS'.

Special Standard 'PWS' designates a public water supply intake. The Board's Water Quality Standards establish numerical standards for specific parameters calculated to protect human health from toxic effects through drinking water and fish consumption. See 9VAC25-260-140.B. for applicable criteria.

16. Antidegradation (9VAC25-260-30):

All state surface waters are provided one of three levels of antidegradation protection. For Tier 1 or existing use protection, existing uses of the water body and the water quality to protect these uses must be maintained. Tier 2 water bodies have water quality that is better than the water quality standards. Significant lowering of the water quality of Tier 2 waters is not allowed without an evaluation of the economic and social impacts. Tier 3 water bodies are exceptional waters and are so designated by regulatory amendment. The antidegradation policy prohibits new or expanded discharges into exceptional waters.

VA0021750 PAGE 5 of 10

The receiving stream has been classified as Tier 1 based on the determination that the critical 7Q10 and 1Q10 flows for the stream are zero. The proposed permit limits have been established by determining wasteload allocations which will result in attaining and/or maintaining all water quality criteria which apply to the receiving stream, including narrative criteria. These wasteload allocations will provide for the protection and maintenance of all existing uses.

17. Effluent Screening, Wasteload Allocation and Effluent Limitation Development:

To determine water quality-based effluent limitations for a discharge, the suitability of data must first be determined. Data is suitable for analysis if one or more representative data points are equal to or above the quantification level ("QL") and the data represent the exact pollutant being evaluated.

Next, the appropriate Water Quality Standards (WQS) are determined for the pollutants in the effluent. Then, the Wasteload Allocations (WLAs) are calculated. In this case since the critical flows 7Q10 and 1Q10 have been determined to be zero, the WLAs are equal to the WQS. The WLA values are then compared with available effluent data to determine the need for effluent limitations. Effluent limitations are needed if the 97th percentile of the daily effluent concentration values is greater than the acute wasteload allocation or if the 97th percentile of the four-day average effluent concentration values is greater than the chronic wasteload allocation. Effluent limitations are based on the most limiting WLA, the required sampling frequency and statistical characteristics of the effluent data.

a. Effluent Screening

Effluent data obtained from the permit application and the February 2009 – May 2013 Discharge Monitoring Reports (DMRs) has been reviewed and determined to be suitable for evaluation.

Please see Attachment 8 for a summary of effluent data.

b. Mixing Zones and Wasteload Allocations (WLAs)

Wasteload allocations (WLAs) are calculated for those parameters in the effluent with the reasonable potential to cause an exceedance of water quality criteria. The basic calculation for establishing a WLA is the steady state complete mix equation:

WLA = $\frac{C_o[Q_e + (f)(Q_s)] - [(C_s)(f)(Q_s)]}{Q_e}$

Where

WLA = Wasteload allocation

C_o = In-stream water quality criteria

 Q_e = Design flow

Q_s = Critical receiving stream flow

(1Q10 for acute aquatic life criteria; 7Q10 for chronic aquatic life criteria; harmonic mean for carcinogen-human health criteria; 30Q10 for ammonia criteria; and 30Q5 for non-carcinogen

human health criteria)

f = Decimal fraction of critical flow

C_s = Mean background concentration of parameter in the receiving stream.

The water segment receiving the discharge via Outfall 001 is considered to have a 7Q10, 30Q10 and 1Q10 of 0.0 MGD. As such, there is no mixing zone and the WLA is equal to the C_0 .

c. Effluent Limitations and Monitoring, Outfall 001 - Toxic Pollutants

9VAC25-31-220.D. requires limits be imposed where a discharge has a reasonable potential to cause or contribute to an instream excursion of water quality criteria. Those parameters with WLAs that are near effluent concentrations are evaluated for limits.

The VPDES Permit Regulation at 9VAC25-31-230.D. requires that monthly and weekly average limitations be imposed for continuous discharges from POTWs and monthly average and daily maximum limitations be imposed for all other continuous non-POTW discharges.

1). Ammonia as N/TKN:

Staff reevaluated the ammonia criteria and concluded that a reduction in the limitation was possible; however, due to antibacksliding provisions, a relaxation in the limit is not allowed based on a change in the criteria alone. Further, this facility has consistently complied with the current limit of 2.0 mg/L. Therefore, it is staff's best professional judgement that the existing ammonia limitations be carried forward with this reissuance for the 0.0063 MGD flow tier. See Attachment 9 for the 2003 criterion development and subsequent limitation derivation.

The facility has a proposed expanded flow of 0.01175 MGD included with this reissuance. Given the facility's past performance in meeting the current ammonia limit of 2.0 mg/L, it is staff's best professional judgement that this limitation also be proposed for the expanded flow tier.

2). Total Residual Chlorine:

Chlorine is used for disinfection and is potentially present in the discharge. Staff calculated WLAs for TRC using current critical flows. In accordance with current DEQ guidance, staff used a default data point of 0.2 mg/L and the calculated WLAs to derive limits. A monthly average of 0.008 mg/L and a weekly average limit of 0.010 mg/L are proposed for both the 0.0063 MGD and 0.01175 MGD facility (see Attachment 10).

3). Metals/Organics:

Given the wastewater sources, it is staff's best professional judgment that these pollutants are not present in appreciable amounts and that limits are not warranted.

d. Effluent Limitations and Monitoring, Outfall 001 - Conventional and Non-Conventional Pollutants

No changes to dissolved oxygen (D.O.), biochemical oxygen demand-5 day (BOD₅), total suspended solids (TSS), ammonia as N and pH limitations are proposed.

Dissolved oxygen and BOD₅ limitations were based upon a stream model conducted in 1969/1970 during the permit issuance. Model documentation is lacking; however, downstream water quality data does not indicate an adverse impact from this facility. Therefore, the existing limitations will be maintained.

It is staff's practice to equate the total suspended solids limits with the BOD₅ limits since the two pollutants are closely related in terms of treatment of domestic sewage.

pH limitations are set at the water quality criteria.

E. coli limitations are in accordance with the Water Quality Standards 9VAC25-260-170.

e. Effluent Limitations and Monitoring Summary

The effluent limitations are presented in the following table. Limits were established for BOD₅, total suspended solids, ammonia as N, pH, dissolved oxygen, E. coli and total residual chlorine.

The limit for total suspended solids is based on best professional judgement.

The mass loading (kg/d) for BOD₅ and TSS monthly and weekly averages were calculated by multiplying the concentration values (mg/L), with the flow values (in MGD) and then by a conversion factor of 3.785.

Sample Type and Frequency (excluding bacteria, See Section 24) are in accordance with the recommendations in the VPDES Permit Manual.

The VPDES Permit Regulation at 9VAC25-31-30 and 40 CFR Part 133 require that the facility achieve at least 85% removal for BOD and TSS (or 65% for equivalent to secondary). The limits in this permit are water quality-based effluent limits and result in greater than 85% removal.

18. Antibacksliding:

All limits in this permit are at least as stringent as those previously established. Backsliding does not apply to this reissuance.

19a. Effluent Limitations/Monitoring Requirements:

Design flow is 0.0063 MGD.

During the period beginning with the permit's effective date and lasting until the issuance of the CTO for the 0.01175 MGD facility or the expiration date, whichever occurs first.

PARAMETER	BASIS FOR	DISCHARGE LIMITATIONS					MONITORING REQUIREMENTS	
•	LIMITS	Monthly Average	Monthly Average Weekly Average Mir		Maximum	Frequency	Sample Type	
Flow (MGD)	NA	NL	NA	NA	NL	1/D	Estimate	
pH	3	NA	NA	6.0 S.U.	9.0 S.U.	1/D	Grab	
BOD ₅	3,5	24 mg/L 0.57 kg/day	36 mg/L 0.86 kg/day	NA	NA	1/M	Grab	
Total Suspended Solids (TSS)	2	24 mg/L 0.57 kg/day	36 mg/L 0.86 kg/day	NA	NA	1/M	Grab	
Dissolved Oxygen (DO)	3,5	NA	` NA	6.0 mg/L	NA	1/ D	Grab	
Ammonia, as N	2,3	2.0 mg/L	2.0 mg/L	NA	NA	1/M	Grab	
E. coli (Geometric Mean) (a)	3,6	126 n/100mL	NA	NA	NA	1/Q (b) (c)	Grab	
Total Residual Chlorine (after contact tank)	4	NA	NA	1.5 mg/L	NA	1/D	Grab	
Total Residual Chlorine (after dechlorination)	3	0.008 mg/L	0.010 mg/L	NA	NA	I/D	Grab	

The basis for the limitations codes are:

1. Federal Effluent Requirements

MGD = Million gallons per day.

I/D = Once every day.

2. Best Professional Judgement

NA = Not applicable.

S.U. = Standard units.

I/M =Once every month.

3. Water Quality Standards

NL = No limit; monitor and report.

1/Q = Once every calendar quarter.

4. DEQ Disinfection Guidance

5. Stream Model (Section 15.d.)

6. Limestone Branch Bacteria TMDL

Estimate = Reported flow is to be based on the technical evaluation of the sources contributing to the discharge.

Grab = An individual sample collected over a period of time not to exceed 15-minutes.

The quarterly monitoring periods shall be January through March, April through June, July through September and October through December. The DMR shall be submitted no later than the 10th day of the month following the monitoring period.

⁽a) Samples shall be collected between the hours of 10 A.M. and 4 P.M.

⁽b) See Section 21.i.

⁽c) The permittee shall collect four (4) weekly samples during one month within each quarterly monitoring period as defined below. The results shall be reported as the geometric mean

19b. Effluent Limitations/Monitoring Requirements:

Design flow is 0.01175 MGD.

During the period beginning with the issuance of the CTO for the 0.01175 MGD facility and lasting until the expiration date.

PARAMETER	BASIS FOR	DISCHARGE LIMITATIONS				MONITORING REQUIREMENTS	
	LIMITS	Monthly Average	Weekly Average	<u>Minimum</u>	<u>Maximum</u>	Frequency	Sample Type
Flow (MGD)	NA	NL	NA	NA	NL	1/D	Estimate
pН	3	NA	NA	6.0 S.U.	9.0 S.U.	1/D	Grab
BOD ₅	3,5	24 mg/L 1.1 kg/day	36 mg/L 1.6 kg/day	NA	NA	1/M	Grab
Total Suspended Solids (TSS)	2	24 mg/L 1.1 kg/day	36 mg/L 1.6 kg/day	NA	NA	1/M	Grab
Dissolved Oxygen (DO)	3,5	NA	NA	6.0 mg/L	NA	1/D	Grab
Ammonia, as N	2,3	2.0 mg/L	2.0 mg/L	NA	NA	1/M	Grab
E. coli (Geometric Mean) (8)	3,6	126 n/100mL	NA	NA	NA	1/Q (b) (c)	Grab
Total Residual Chlorine (after contact tank)	4	NA	NA	1.5 mg/L	NA	1/D	Grab
Total Residual Chlorine (after dechlorination)	3	0.008 mg/L	0.010 mg/L	NA	NA	l/D	Grab

The basis for the limitations codes are:

1	Endoual	E-601	Requirements
1.	rederat	CHUIETI	Reduirements

2. Best Professional Judgement

3. Water Quality Standards

4. DEQ Disinfection Guidance

5. Stream Model (Section 15.d.)

MGD = Million gallons per day.

NA = Not applicable.

NL = No limit; monitor and report.

S.U. = Standard units.

I/D = Once every day.

1/M = Once every month.

1/Q = Once every calendar quarter.

6. Limestone Branch Bacteria TMDL

Estimate = Reported flow is to be based on the technical evaluation of the sources contributing to the discharge.

Grab = An individual sample collected over a period of time not to exceed 15-minutes.

The quarterly monitoring periods shall be January through March, April through June, July through September and October through December. The DMR shall be submitted no later than the 10th day of the month following the monitoring period.

⁽a) Samples shall be collected between the hours of 10 A.M. and 4 P.M.

⁽b) See Section 21.i.

⁽c) The permittee shall collect four (4) weekly samples during one month within each quarterly monitoring period as defined below. The results shall be reported as the geometric mean.

VA0021750 PAGE 9 of 10

20. Other Permit Requirements:

Part I.B. of the permit contains additional chlorine monitoring requirements, quantification levels and compliance reporting instructions

These additional chlorine requirements are necessary per the Sewage Collection and Treatment Regulations at 9VAC25-70 and by the Water Quality Standards at 9VAC25-260-170. Minimum chlorine residual must be maintained at the exit of the chlorine contact tank to assure adequate disinfection. No more that 10% of the monthly test results for TRC at the exit of the chlorine contact tank shall be < 1.5 mg/L with any TRC < 0.6 mg/L considered a system failure. *E. coli* limits are defined in this section as well as monitoring requirements to take effect should an alternate means of disinfection be used.

9VAC25-31-190.L.4.c. requires an arithmetic mean for measurement averaging and 9VAC25-31-220.D. requires limits be imposed where a discharge has a reasonable potential to cause or contribute to an in-stream excursion of water quality criteria. Specific analytical methodologies for toxics are listed in this permit section as well as quantification levels (QLs) necessary to demonstrate compliance with applicable permit limitations or for use in future evaluations to determine if the pollutant has reasonable potential to cause or contribute to a violation. Required averaging methodologies are also specified.

21. Other Special Conditions:

- a. <u>95% Capacity Reopener</u>. The VPDES Permit Regulation at 9VAC25-31-200.B.4 requires all POTWs and PVOTWs develop and submit a plan of action to DEQ when the monthly average influent flow to their sewage treatment plant reaches 95% or more of the design capacity authorized in the permit for each month of any three consecutive month period. This facility is a POTW.
- b. <u>Indirect Dischargers</u>. Required by VPDES Permit Regulation, 9VAC25-31-200.B.1 and B.2 for POTWs and PVOTWs that receive waste from someone other than the owner of the treatment works.
- c. O&M Manual Requirement. Required by Code of Virginia §62.1-44.19; Sewage Collection and Treatment Regulations, 9VAC25-790; VPDES Permit Regulation, 9VAC25-31-190.E. The permittee shall maintain a current Operations and Maintenance (O&M) Manual. The permittee shall operate the treatment works in accordance with the O&M Manual and shall make the O&M Manual available to Department personnel for review upon request. Any changes in the practices and procedures followed by the permittee shall be documented in the O&M Manual within 90 days of the effective date of the changes. Non-compliance with the O&M Manual shall be deemed a violation of the permit.
- d. <u>CTC, CTO Requirement</u>. The Code of Virginia § 62.1-44.19; Sewage Collection and Treatment Regulations, 9VAC25-790 requires that all treatment works treating wastewater obtain a Certificate to Construct prior to commencing construction and to obtain a Certificate to Operate prior to commencing operation of the treatment works.
- e. <u>Licensed Operator Requirement</u>. The Code of Virginia at §54.1-2300 et seq. and the VPDES Permit Regulation at 9VAC25-31-200.C, and Rules and Regulations for Waterworks and Wastewater Works Operators (18VAC160-20-10 et seq.) requires licensure of operators. This facility requires a Class IV operator.
- f. Reliability Class. The Sewage Collection and Treatment Regulations at 9VAC25-790 require sewage treatment works to achieve a certain level of reliability in order to protect water quality and public health consequences in the event of component or system failure. Reliability means a measure of the ability of the treatment works to perform its designated function without failure or interruption of service. The facility is required to meet Class II reliability.
- g. <u>Sludge Reopener</u>. The VPDES Permit Regulation at 9VAC25-31-220.C. requires all permits issued to treatment works treating domestic sewage (including sludge-only facilities) include a reopener clause allowing incorporation of any applicable standard for sewage sludge use or disposal promulgated under Section 405(d) of the CWA. The facility includes a sewage treatment works.
- h. <u>Sludge Use and Disposal</u>. The VPDES Permit Regulation at 9VAC25-31-100.P; 220.B.2., and 420 through 720 and 40 CFR Part 503 require all treatment works treating domestic sewage to submit information on their sludge use and disposal practices and to meet specified standards for sludge use and disposal. The facility includes a treatment works treating domestic sewage.
- i. <u>Bacteria Monitoring Frequency</u>. If the facility exceeds the geometric mean for *E. coli* during a sampling period, then the monitoring frequency of once per week shall become effective upon written notice from DEQ for a minimum period of 30 days. The permittee may request the reduced monitoring frequency be reinstated upon demonstration of compliance for a given month.
- j. <u>TMDL Reopener</u>. This special condition allows the permit to be reopened if necessary to bring it into compliance with any applicable TMDL that may be developed and approved for the receiving stream.

VPDES PERMIT PROGRAM FACT SHEET

VA0021750 PAGE 10 of 10

22. <u>Permit Section Part II</u>. Part II of the permit contains standard conditions that appear in all VPDES Permits. In general, these standard conditions address the responsibilities of the permittee, reporting requirements, testing procedures and records retention.

23. Changes to the Permit from the Previously Issued Permit:

- a. Special Conditions:
 - > The Bacteria Monitoring Frequency special condition was included with this reissuance.
- b. Monitoring and Effluent Limitations:
 - > See Section 21.i. and Section 24 of this Fact Sheet.

24. Variances/Alternate Limits or Conditions:

The permittee submitted a written request to DEQ-NRO for a reduction in the sampling frequency for *E. coli* to once per quarter during the last permit term. The request was approved by DEQ-NRO staff and there have been no excursions reported at the 0.0063 MGD flow tier. Therefore, the permittee shall continue collecting four (4) samples during one month within each quarterly monitoring period as defined in Sections 19.a. and 19.b. of this Fact Sheet. The results shall be reported as the geometric mean.

It is staff's best professional judgement, based on the performance of this facility, that the reduction could be applied at the expanded flow tier of 0.01175 MGD as well.

25. Public Notice Information:

First Public Notice Date:

17 July 2013

Second Public Notice Date:

24 July 2013

Public Notice Information is required by 9VAC25-31-280.B. All pertinent information is on file and may be inspected, and copied by contacting the: DEQ Northern Regional Office; 13901 Crown Court, Woodbridge, VA 22193; Telephone No. (703) 583-3873; Douglas.Frasier@deq.virginia.gov. See Attachment 11 for a copy of the public notice document.

Persons may comment in writing or by email to the DEQ on the proposed permit action, and may request a public hearing, during the comment period. Comments shall include the name, address, and telephone number of the writer and of all persons represented by the commenter/requester, and shall contain a complete, concise statement of the factual basis for comments. Only those comments received within this period will be considered. The DEQ may decide to hold a public hearing, including another comment period, if public response is significant and there are substantial, disputed issues relevant to the permit. Requests for public hearings shall state 1) the reason why a hearing is requested; 2) a brief, informal statement regarding the nature and extent of the interest of the requester or of those represented by the requester, including how and to what extent such interest would be directly and adversely affected by the permit; and 3) specific references, where possible, to terms and conditions of the permit with suggested revisions. Following the comment period, the Board will make a determination regarding the proposed permit action. This determination will become effective, unless the DEQ grants a public hearing. Due notice of any public hearing will be given. The public may request an electronic copy of the draft permit and fact sheet or review the draft permit and application at the DEQ Northern Regional Office by appointment.

26. Additional Comments:

Previous Board Action(s):

None.

Staff Comments:

None received.

Public Comment:

No comments were received during the public notice.

Fact Sheet Attachments Table of Contents

Lucketts Elementary School VA0021750 2014 Reissuance

Attachment 1	Flow Frequency Determination
Attachment 2	Facility Schematic/Diagram
Attachment 3	Topographic Map
Attachment 4	Site Inspection Report Summary
Attachment 5	Planning Statement
Attachment 6	Water Quality Criteria / Wasteload Allocation Analysis for 0.0063 MGD Facility
Attachment 7	Water Quality Criteria / Wasteload Allocation Analysis for 0.01175 MGD Facility
Attachment 8	February 2009 – May 2013 Effluent Data
Attachment 9	Ammonia Limitation Derivation
Attachment 10	Total Residual Chlorine Limitation Derivation
Attachment 11	Dublic Notice

NEMORANDUM

DEPARTMENT OF ENVIRONMENTAL QUALITY - WATER DIVISION
Water Quality Assessments and Flanning
629 E. Main Street P.O. Box 10009 Richmond, Virginia 23240

SUBJECT: Flow Frequency Determination

Luckettes Elementary School STP - #VA0021750

TO: James C. Engbert, NRO

FROM: Paul E. Herman, P.E., WQAP

DATE: June 22, 1998

COPIES: Ron Gregory, Charles Martin, File

Northern VA. Ragion Dapt. of Env. Quality

JUN 24 1998

This memo supercedes my June 15, 1993 memo to Joan Crowther Concerning the subject VPDES permit.

The Luckettes Elementary School STP discharges to an unnamed tributary of Limestone Branch near Luckettes, VA. Stream flow frequencies are required at this site by the permit writer for the purpose of calculating effluent limitations for the VPDES permit.

The values at the discharge point were determined by inspection of the USGS Waterford Quadrangle topographical map which shows the receiving stream as intermittent at the discharge point. The flow frequencies for intermittent streams are 0.0 cfs for the 1010, 7010, 3005, high flow 1010, high flow 7010, and the harmonic mean. The drainage area above the discharge point is 0.14 mi². For modeling purposes, flow frequencies have been determined for the first perennial reach downstream of the outfall. This occurs on the same unnamed tributary approximately 2000 feet downstream of the outfall.

The USGS conducted several flow measurements on a this unnamed tributary to Limestone Branch from 1979-1980. The measurements were made approximately 3.0 miles downstream of the discharge point at the Route 661 bridge. The measurements made by the USGS correlated very well with the same day daily mean values from the continuous record gage on Catoctin Creek near Taylorstown, VA #01638480. The measurements and daily mean values were plotted on a logarithmic graph and a best fit line was drawn through the data points. The required flow frequencies from the reference gage were plotted on the regression line and the associated flow frequencies at the measurement site were determined from the graph.

The flow frequencies at the discharge point were determined by using the values at the measurement site and adjusting them by proportional drainage areas. The data for the reference gage, the measurement site and the discharge point are presented below:

Attachment I

Catootin Creek at Taylorstown, VA (#01638480):

		1	Drainage	Area	= 89	.6 mi	!			
1010	=					Flow		=	4.6	cfs
7010	=	1.1	cfs		High	Flow	7010	=	6.5	cfs
3005	=	3.8	cfs				HM	=	18	cfs

UT to Limestone Branch at measurement site (#01643600):


		D 1	rainage	Area	= 5.8	32 mi ²	!			
1010	=	0.22	cfs -			Flow				
7Q10	=	0.28	cfs		High	Flow	7010	=	0.90	cfs
30Q5	•	0.63	cfs	•	-		HM	=	1.8	cfs


UT to Limestone Branch at perennial point:

-	Drainage	Area	≈ 0.8	36 mi³	!			
1010 =	0.028 cfs					===	0.091	cfs
7Q10	0.035 cfs		High	Flow	7Q10	=	0.11	cfs
30Q5 =	0.079 cfs				HM	=	0.23	cfs

This analysis assumes there are no significant discharges, withdrawals or springs influencing the flow in unnamed tributary to Limestone Branch above the perennial point.

If there are any questions concerning this analysis, please let me know.





Attachment 3

Problems identified at last inspection:	-	
None noted.		
		 <u> </u>

SUMMARY

Comments:

• The plant is well maintained and appears to be good condition. Recordkeeping is thorough and well organized.

Recommendations for action:

• Infiltration of groundwater into the dechlorination tablet feeder vault may affect sample results though dilution of the final effluent or by introducing contaminants if it enters the sample box. The infiltration points in the vault and/or discharge lines should be identified and repaired. The chlorine contact tank should also be checked for ground water infiltration.

To:

Douglas Frasier

From:

Jennifer Carlson

Date:

5 June 2013

Subject:

Planning Statement for Lucketts Elementary School

Permit Number:

VA0021750

Information for Outfall 001:

Discharge Type:

Municipal, minor

Discharge Flower

0.0063 MGD with expansion to 0.01175

Receiving Stream:

Limestone Branch, UT

Latitude / Longitude: 🚁

39° 12' 47" / 77° 31' 56"

Rivermile:

3.69

Streamcode:

1aXAQ

Waterbody:

VAN-A03R

Water Quality Standards:

Class III, Section 8, PWS

Drainage Area

 $0.14 \, \text{mi}^2$

1. Please provide water quality monitoring information for the receiving stream segment. If there is not monitoring information for the receiving stream segment, please provide information on the nearest downstream monitoring station, including how far downstream the monitoring station is from the outfall.

The facility discharges to a segment of the unnamed tributary to Limestone Branch (1aXAQ), that has not been monitored or assessed by DEQ. However, there is a DEQ monitoring station on the unnamed tributary to Limestone Branch located approximately 2.8 miles downstream of Outfall 001. Monitoring station 1aXAQ000.85 is located at the Rt. 661 bridge crossing. The following is the water quality summary for the downstream portion of the unnamed tributary, as taken from the Draft 2012 Integrated Report*:

The following are the DEQ ambient monitoring stations located on the unnamed tributary to Limestone Branch:

• 1aXAQ000.85, at Route 661.

E. coli monitoring finds a bacteria impairment, resulting in an impaired classification for the recreation use. This impairment is nested within the downstream completed bacteria TMDL for Limestone Branch.

The aquatic life use is fully supporting, however an observed effect for the aquatic life use is noted as citizen monitoring finds a medium probability of adverse conditions for biota. The wildlife use is considered fully supporting.

The fish consumption and public water supply uses were not assessed.

^{*}Virginia's Draft 2012 Integrated Report (IR) has been through the public comment period and reviewed by EPA. The 2012 IR is currently awaiting final approval.

2. Does this facility discharge to a stream segment on the 303(d) list? If yes, please fill out Table A.

No.

3. Are there any downstream 303(d) listed impairments that are relevant to this discharge? If yes, please fill out Table B.

Yes.

Table B. Information on Downstream 303(d) Impairments and TMDLs

Name	Impaired Use Information in	Cause the Draft 2012 Inte	Distance From Outfall grated Repo	completed		Basis for WLA	
Unnamed Tributary to Limestone Branch	Recreation	E. coli	1.7 miles	Limestone Branch Bacteria 7/6/2004	2.05E+10 cfu/year <i>E. coli</i>	126 cfu/100ml <i>E. coli</i> 0.01175 MGD	TMDL modified 9/24/08 & 3/10/10

^{*}Virginia's Draft 2012 Integrated Report (IR) has been through the public comment period and reviewed by EPA. The 2012 IR is currently awaiting final approval.

4. Is there monitoring or other conditions that Planning/Assessment needs in the permit?

There is a completed downstream TMDL for the aquatic life use impairment for the Chesapeake Bay. However, the Bay TMDL and the WLAs contained within the TMDL are not addressed in this planning statement.

5. Fact Sheet Requirements – Please provide information regarding any drinking water intakes located within a 5 mile radius of the discharge point.

There are no public water supply intakes located within 5 miles of this discharge.

FRESHWATER WATER QUALITY CRITERIA / WASTELOAD ALLOCATION ANALYSIS

Facility Name:

Lucketts Elementary

Permit No.: VA0021750

Receiving Stream:

Early Life Stages Present Y/N? =

Limestone Branch, UT

Version: OWP Guidance Memo 00-2011 (8/24/00)

Stream Information		Stream Flows	Mixing Information		Effluent Information	
Mean Hardness (as CaCO3) =	mg/L	1Q10 (Annual) = 0 MGD	Annual - 1Q10 Mix =	% %	Mean Hardness (as CaCO3) =	150 mg/L
90% Temperature (Annual) =	deg C	7Q10 (Annual) = 0 MGD	- 7Q10 Mix =	%	90% Temp (Annual) =	25 deg C
90% Temperature (Wet season) =	deg C	30Q10 (Annual) = 0 MGD	- 30Q10 Mix =	<i>9</i> %	90% Temp (Wet season) =	15 deg C
90% Maximum pH =	S∪	1Q10 (Wet season) = 0 MGD	Wet Season - 1Q10 Mix =	.%	90% Maximum pH =	7 SU
10% Maximum pH =	S∪	30Q10 (Wet season) 0 MGD	- 30Q10 Mix =	%	10% Maximum pH ≔	6.6 SU
Tier Designation (1 or 2) =		30Q5 = 0 MGD			Discharge Flow =	0:0063 MGD
Public Water Supply (PWS) Y/N? =	i Sanaka Y	Harmonic Mean = 0, MGD			-	
Trout Present Y/N? =	- (

(ug/I unless noted) Acenapthene Acrolein	Conc.	Acule	Chronic								Antidegrada			A							
•	0		CHIONIC	HH (PWS)	HH	Acute	Chronic.	HH (PWS)	НН	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн
Acrolein		-	_	6.7E+02	9.9E+02	-	-	6.7E+02	9.9E+02	_	-	-	-	_	-		_	_	-	6.7E+02	9.95+02
	0		_	6.1E+00	9.3E+00		_	6.1E+00	9.3E+00	-	-	-	_	-		_	-	_	-	6.1E+00	9.3E+0
Acrylonitrile ^c	0		-	5.1E-01	2.5E+00	_	-	5.1E-01	2.5E+00	-	-	_	_	-	-	-				5.1E-01	2.5E+00
Aldrin ^C	o 🤚	3.0E+00	-	4.9E-04	5.0E-04	3.0E+00	_	4.9E-04	5.0E-04	_	_			1 -	-	-		3.0E+00		4.9E-04	6.0E-04
Ammonia-N (mg/l) Yearly)	ò	3.61E+01	3.01E+00		-	3.61E+01	3.01E+00	-	-	-		_		-	_		_	3.61E+01	3.01E+00		
mmonia-N (mg/l) High Flow)	» o	3.61E+01	5,73E+00	_	_	3.61E+01	5.73E+00	-	-	-	_	-	_	-	-	-		3.61E+01	6.73E+00	- ,	••
Anthracene	0	-	. -	8.3E+03	4.0E+04	-	-	8.3E+03	4.0E+04	-	-			_	-	-	_		-	8.3E+03	4.0E+04
Antimony	0	**	-	5.6E+00	6.4E+02	_	-	5.6E+00	6.4E+02	-	-	-	-	_		-	-			5.6E+00	6.4E+02
Arsenic	0.	3.4E+02	1.5E+02	1.0E+01	-	3.4E+02	1.5E+02	1.0E+01		-	-	-		-	-		_	3.4E+02	1.5E+02	1.0E+01	
Barium '	0	-	-	2.0E+03				2.0E+03		-	-	-	-	-	-	_		_		2.0E+03	
Benzene ^C	jij jos u	-	-	2.2E+01	5.1E+02	-	-	2.2E+01	5.1E+02	-	-	-		-	••	_				2.2E+01	5.1E+02
Benzidine ^c	0	-		8.6E-04	2.0E-03	_	_	8.6E-04	2.0E-03	_	_			-	_	_	_		-	8.6E-04	2.0E-03
Benzo (a) anthracene ^c	0 4	-	_	3.8E-02	1.8E-01			3.8E-02	1.8E-01			-	-	-	_	_			_	3.8E-02	1.8E-01
Benzo (b) fluoranthene ^c	o			3.8E-02	1.8E-01	_	_	3.8E-02	1.8E-01		-	-	-						••	3.8E-02	1.8E-01
Benzo (k) fluoranthene ^c	\$\$100 June 18		-	3.8E-02	1.8E-01	-	-	3.8E-02	1.8E-01	-	-	_		~	_	_	_	_	_	3.8E-02	1.8E-01
Benzo (a) pyrene ^c	0-	_	.	3.8E-02	1.8E-01	-	-	3.8E-02	1.8E-01		_	-		_	-	_		_	_	3.8E-02	1.8E-01
Bis2-Chloroethyl Ether ^c	, o .	-	_	3.0E-01	5.3E+00	-	-	3.0E-01	5.3E+00	-	-	_	_	-	_		_	_		3.0E-01	5.3E+00
Bis2-Chioroisopropyl Ether	. 0		_	1.4E+03	6.5E+04	-	-	1.4E+03	6.5E+04		-	_	-	_	_		-			1.4E+03	6.5E+04
Bis 2-Ethylhexyl Phthalate ^c	(O)	-	-	1.2E+01	2.2E+01			1.2E+01	2.2E+01	_	-	-	-	-	_	·	-	}	••	1.2E+01	2.2E+01
Bromoform ^C	. 0	-	-	4.3E+01	1.4E+03	_	_	4.3E+01	1.4E+03	_	_	_	_	-	-		_	_		4.3E+01	1.4E+03
Distribenzylphthalate	3 O	_	-	1.5E+03	1.9E+03	_	_	1.5E+03	1.9E+03			_	-		_	_	_	۱		1.5E+03	1.9E+03
muir 🗲	. 0	6.2E+00	1.6E+00	5.0E+00		6.2E+00	1.6E+00	5.0E+00	_	-	_	_	_		-	-	_	6.2E+00	1.6E+00	5.0E+00	
on Tetrachlonde ^c		-	· -	2.3E+00	1.6E+01	_	_	2.3E+00	1.6E+01	_		-	_	_	_	_				2.3E+00	1.6E+01
🔼 dane "	0 8x	2.4E+00	4.3E-03	8.0E-03	8.1E-03	2.4E+00	4.3E-03	8.0E-03	8.1E-03				_		-	_	_	2.4E+00	4.3E-03	8.0E-03	8.1E-03
ide	0	8.6E+05	2.3E+05	2.5E+05	_	8.6E+05	2.3E+05	2.5E+05	_	_	_	_	_		_	_	_	8.6E+05	4.3E+05		
	0	1.9E+01	1.1E+01			1.9E+01	1.1E+01		_		_	_		_	_	_	_			2.5E+05	••
© obenzene	0		-	1.3E+02	1.6E+03			1.3E+02	1.6E+03		_	~	-	_	_	-	-	1.9E+01	1.1E+01	1.3E+02	 1.6E+03

						·														
Parameter	Background	ļ		ality Criteria	,,		Wasteloa	d Allocations			Antidegradation Base	eline	A	\ntidegradati	on Allocations			Most Limiti	ng Allocation:	
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН	Acute	Chronic HH (PW	/S) HH	Acute	Chrenic	HH (PW\$)	НН	Acute	Chronic	HH (PWS)	нн
Chlorodibromomethane ^C	0	-	-	4.0E+00	1.3E+02	-		4.0E+00	1.3E+02	-		-	-	_	_		_	_	4.0E+00	1.3E+02
Chloroform	0	-		3.4E+02	1.1E+04	-	-	3.4E+02	1.1E+04	_			-	-	_		_		3.4E+02	1.1E+04
2-Chloronaphthalene	0	-	•	1.0E+03	1.6E+03	-	-	1.0E+03	1.6E+03	-	- -	-	-	-		_	_		1.0E+03	1.6E+03
2-Chlorophenol	30.	-	. –	8.1E+01	1.5E+02	_	-	8.1E+01	1.5E+02	-		_	-		-	-	-		8.1E+01	1.5E+02
Chlorpyrifos	0	8.3E-02	4.1E-02		-	8.3E-02	4.1E-02		-			-	-	_	-	-	8.3E-02	4.1E-02		=-
Chromium IfI	0	7.9E+02	1.0E+02	_	-	7.9E+02	1.0E+02	-	-	-	- -		i -		· 	-	7.9E+02	1.0E+02	-	
Chromium VI	. 0	1.6E+01	1.1E+01		-	1.6E+01	1.1E+01	**	-	-		-			_		1.6E+01	1.1E+01		
Chromium, Total	0	-	-	1.0E+02	-	-	-	1.0E+02	-	-		-	-	-			-		1.0E+02	~
Chrysene ^c	0		-	3.8E-03	1.8E-02	-	-	3.8E-03	1.8E-02	_		-	-	-			-	_	3.8E-03	1.8E-02
Copper	0	2.0E+01	1.3E+01	1.3E+03		2.0E+01	1.3E+01	1.3E+03	-	_		-	-	_	_	-	2.0E+01	1.3E+01	1.3E+03	
Cyanide, Free	0	2.2E+01	5.2E+00	1.4E+02	1.6E+04	2.2E+01	5.2E+00	1.4E+02	1.6E+04	-		-	-	-	-	_	2.2E+01	5.2E+00	1.4E+02	1.6E+04
DDD °	. 0	-	-	3.1E-03	3.1E-03	-	-	3.1E-03	3.1E-03		- . -	-	-		-	-			3.1E-03	3.1E-03
DDE c	. 0	-	-	2.2E-03	2.2E-03	-	-	2.2E-03	2.2E-03			-	-		-	-	-		2.2E-03	2.2E-03
DDT ^c	0	1.1E+00	1.0E-03	2.2E-03	2.2E-03	1.15+00	1.0E-03	2.2E-03	2.2E-03	_		-	-	-	-		1.1E+00	1.0E-03	2.2E-03	2.2E-03
Demeton	0	-	1.0E-01	-	-	-	1.0E-01	-	-			-	-	-	**	••		1.0E-01		-
Diazinon	0	1.7E-01	1.7E-01	_	-	1.7E-01	1.7E-01		-	_		-	-		-	-	1.7E-01	1.7E-01		
Dibenz(a,h)anthracene ^C	0	-	-	3.8E-02	1.8E-01	-	-	3.8É-02	1.BE-01	••		-	-		-				3.8E-02	1.8E-01
1,2-Dichlorobenzene	0	-	•-	4.2E+02	1.3E+03	-	-	4.2E+02	1.3E+03			-	-	_	-	-	-		4.2E+02	1.3E+03
1,3-Dichlorobenzene	0.	-	-	3.2E+02	9.6E+02	-	••	3.2E+02	9.6E+02	-		-	-	-	-	-			3.2E+02	9.6E+02
1,4-Dichlorobenzene	0		~	6.3E+01	1.9E+02	-	-	6.3E+01	1.9E+02			_	-	-	•-	-		-	6.3E+01	1.9E+02
3,3-Dichlorobenzidine ^c	o.	-		2.1E-01	2.8E-01	-	-	2.1E-01	2.8E-01			-	-	•-	-				2.1E-01	2.BE-01
Dichlorobromomethana ^C	0	-	-	5.5E+00	1.7E+02	-	-	5.5E+00	1.7E+02	-		-	-	-					5.5E+00	1.7E+02
1,2-Dichloroethane ^C	0			3.8E+00	3.7E+02	-	-	3.8E+00	3.7E+02	-			-			-		-	3.8E+00	3.7E+02
1,1-Dichloroethylene	0	_	-	3.3E+02	7.1E+03	-		3.3E+02	7.1E+03	-			-	-	-			-	3.3E+02	7.1E+03
1,2-trans-dichloroethylene	0	-	÷	1.4E+02	1.0E+04	-	-	1.4E+02	1.0E+04	-		-	-	-	-			-	1.4E+02	1.0E+04
2,4-Dichlorophenol 2,4-Dichlorophenoxy	0			7.7E+01	2.9E+02	-		7.7E+01	2.9E+02					-	-			-	7.7E+01	2.9E+02
acetic acid (2.4-D)	0		-	1.0E+02		-	_	1.0E+02	-	_		_	_		~	_	_	-	1.0E+02	**
1,2-Dichloropropane ^c	5 O		-	5.0E+00	1.5E+02	-	-	5.0E+00	1.5E+02			· –	_		_		-	-	5.0E+00	1.6E+02
1,3-Dichloropropene ^c	0	· -		3.4E+00	2.1E+02	-		3.4E+00	2.1E+02				-	-	-		_		3.4E+00	2.1E+02
Dieldrin ^C		2.4E-01	5.6E-02	5.2E-04	5.4E-04	2.4E-01	5.6E-02	5.2E-04	5.4E-04	-		-				-	2.4E-01	5.6E-02	5.2E-04	5.4E-04
Diethyl Phthalate	. 0	-		1.7E+04	4.4E+04	-	-	1.7E+04	4.4E+04	-			-		-	-	_		1.7E+04	4.4E+04
2,4-Dimethylphenol	် o ်		-	3.8E+02	8.5E+02	_	-	3.8E+02	8.5E+02			-			_			_	3.8E+02	8.5E+02
Dimethyl Phthalate	0		-	2.7E+05	1.1E+06	-	-	2.7E+05	1.1E+06	-			-	_			_		2.7E+05	1.1E+06
Di-n-Butyl Phthalate	0	-		2.0E+03	4.5E+03		-	2.0E+03	4.5E+03			-	-	_		_			2.0E+03	4.5E+03
2,4 Dinitrophenol	0	- '	-	6.9E+01	5.3E+03	_	-	6.9E+01	5.3E+03	_		-	-	-		-	_		6.9E+01	5.3E+03
2-Methyl-4,6-Dinitrophenol	.0	-		1.3E+01	2.8E+02	-	-	1.3E+01	2.8E+02	_			-	_				••	1,3E+01	2.8E+02
2,4-Dinitrotoluene ^c	0	-	_	1.1E+00	3.4E+01	-		1.1E+00	3.4E+01	-		n	-	_	-	_		_	1.1E+00	3.4E+01
Dioxin 2,3,7,8- tetrachlorodibenzo-p-dioxin	0	_	÷	5.0E-08	5.1E-08			5.0E-08	5.1E-08							l				
1,2-Diphenylhydrazine ^C	· 化合理 (1)		-	3.6E-01	2.0E+00		_	3.6E-01	2.0E+00	_		-	_		•	_ [-	6.0E-08	5.1E-08
Alpha-Endosulfan	0	2.2E-01	5.6E-02	6.2E+01	8.9E+01	2.2E-01	5.6E-02	6.2E+01	8.9E+01	-		_	-	_	_	-			3.6E-01	2.0E+00
Beta-Endosulfan	D	2.2E-01	5.6E-02	6.2E+01	8.9E+01	2.2E-01	5.6E-02	6.2E+01	8.9E+01	_		_	~			-	2.2E-01	5.6E-02	6.2E+01	8.9E+01
Alpha + Beta Endosulfan	0	2.2E-01	5.6E-02	-	-	2.2E-01	5.6E-02	u.26+01	- 0.95.701	_		_	_		-	-	2.2E-01	6.6E-02	6.2E+01	8.9E+01
Endosulfan Sulfate	0		-	6.2E+01	8.9E+01		-	6.2E+01	8.9E+01	_		_		-			2.2E-01	5.6E-02		-
Endrin	0 -	8,6E-02	3.6E-02	5.9E-02	6.0E-02	8.6E-02	3.6E-02	5.9E-02	6.0E-02	-		-	_		_	-			6.2E+01	8.9E+01
Endrin Aldehyde	0		-	2.9E-01	3.0E-01	_	-	2.9E-01	3.0E-01					_	-	-	8.6E-02	3.6E-02	5.9E-02	6.0E-02
		<u> </u>		2.02-01	J.J.C 0 1			2.01	0,06-01						-	_			2.9E-01	3.0E-01

Parameter	Background		Water Qu	ality Criteria			Wasteloa	d Allocations			Antidegrada	ation Baseline		A	ntidegradati	on Allocations		1	Most I imiti	ng Allocation	15
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн
Ethylbenzene	0.	-	<u> </u>	5.3E+02	2.1E+03		_	5.3E+02	2.1E+03					-	T OTH OTHE	-			Lemonic		2.1E+03
Fluoranthene	0	_	_	1.3E+02	1.4E+02	_	_	1.3E+02	1.4E+02	_	_	_	_	i _		_	_	"	_	5.3E+02	
Fluorene	0	_		1.1E+03	5.3E+03	· _		1.1E+03	5.3E+03	_	_	_			_	-	~	"		1.3E+02	1.4E+02
Foaming Agents	- 0			5.0E+02	_	_		5.0E+02	J.JL • Q.J	_	_	_	-	-	-	-	_	- .	-	1.1E+03	5.3E+03
Guthion	4 0: 4		1.0E-02	0.02.02	_			3.06702		_		-	_	-	-		-	_	-	5.0E+02	
Heptachlor ^C		50504		-			1.0E-02			-		-	_	-	-		-	-	1.0E-02	••	
l .	0	5.2E-01	3.8E-03	7.9E-04	7.9E-04	5.2E-01	3.8E-03	7.9E-04	7.9E-04	_	**		-	-	••	_	-	5.2E-01	3.8E-03	7.9E-04	7.9E-04
Heptachlor Epoxide ^c	0.	5.2E-01	3.8E-03	3.9E-04	3.9E-04	5.2E-01	3.8E-03	3.9E-04	3.9E-04		-	-		-	-	-		5.2E-01	3.8E-03	3.9E-04	3.9E-04
Hexachlorobenzene ^C	.º	-	-	2.8E-03	2.9€-03	-	-	2.8E-03	2.9E-03	-	-	-	-	-	••	-	-	-		2.8E-03	2.9E-03
Hexachtorobutadiene	0	-		4.4E+00	1.8E+02	-		4.4E+00	1.8E+02	-	-	-	••	-	-	-	-	-	-	4.4E+00	1.8E+02
Hexachlorocyclohexane Alpha-BHC ^C	0 0			0.65.00	4.05.00	[0.05.00	4.05.00												
Hexachiorocyclohexane	V. 19	_		2.6E-02	4.9E-02	-	-	2.6E-02	4.9E-02	-		-		-	-	-		-	-	2.6E-02	4.9E-02
Beta-BHC ^C	G 0	_		9.1E-02	1.7E-01	_	_	9.1E-02	1.7E-01	_			_	_	_	_	_	1		0.45.00	4 75 04
Hexachiorocyclohexane								0.12 02					_	_		_	_	i -	_	9.1E-02	1.7E-01
Gamma-BHC ^C (Lindane)	- 0	9.5E-01		9.8E-01	1.8E+00	9.5E-01		9.8E-01	1.8E+00	-	_	_	_	_	_		_	9.5E-01		9.8E-01	1.8E+00
Hexachiorocyclopentadiene	0		_	4.0E+01	1.1E+03			4.0E+01	1.1E+03	_	_				_	_			_	4.0E+01	1.1E+03
Hexachloroethane ^C	0	-	_	1.4E+01	3.3E+01	_	_	1.4E+01	3.3E+01		_	_	_	_	_				-	1.4E+01	3.3E+01
Hydrogen Sulfide	0		2.0E+00				2.0E+00					_	_		_				2.0E+00		
Indeno (1,2,3-cd) pyrene ^C	0 7	_	_	3.8E-02	1.8E-01	_		3.8E-02	1.8E-01	_	_	_		<u> </u>		••	_		2.02+00	***	4.05.04
l.	0	_	_	3.0E+02	1.02-01	_	-	3.0E+02		_	_	_		_		_	-	-	-	3.8E-02	1.8E-01
Iron Isophorone ^c	1	_	_		0.05.00	_	-			••		-		_	_	-		-	-	3.0E+02	-
	0 /	_	_	3.5E+02	9.6E+03			3,5E+02	9.6E+03	-	-	-	_	-	-	-	-	-	-	3.5E+02	9.6E+03
Kepone	0		0.0E+00	-	-		0.0E+00	-	-	-	_	-	-	_	-	_	-		0,0E+00	-	
Lead	0 /	2.0E+02	2.3E+01	1.5E+01	- ·	2.0E+02	2.3E+01	1.5E+01	-	-		••	-	-	-	-	••	2.0E+02	2.3E+01	1.5E+01	
Malathion	0 1	-	1.0E-01	-	-	-	1.0E-01		-	-		~	-	_		-			1.0E-01	••	
Manganese	0	1	••	5.0E+01		-	-	5.0E+01	-	-		-	-	-	_	-	~	-	-	5.0E+01	
Mercury	0	1.4E+00	7.7E-01			1.4E+00	7.7E-01			-	-	**	_	-	••	-		1.4E+00	7.7E-01		
Methyl Bromide	0'		-	4.7E+01	1.5E+03	-	-	4.7E+01	1.5E+03		_	_	-	-	_	-	-	-		4.7E+01	1.5E+03
Methytene Chloride ^c	0 · ·		••	4.6E+01	5.9E+03	-	-	4.6E+01	5.9E+03	-	_	-		-	-	_	_		_	4.6E+01	5.9E+03
Methoxychlor	0		3.0E-02	1.0E+02	-	-	3.0E-02	1.0E+02	-	_	-	-		-	_	-	_		3.0E-02	1.0E+02	
Mirex	0	-	0.0E+00	-	_	-	0.0E+00	_				_		_	_	_			0.0E+00	**	
Nickel	Ö	2.6E+02	2.9E+01	6.1E+02	4.6E+03	2.6E+02	2.9E+01	6.1E+02	4.6E+03	**	_	_	_	_		_		2.6E+02	2.9E+01	6.1E+02	4.6E+03
Nitrate (as N)	0	-	-	1.0E+04			_	1.0E+04	_	_	_	_			_		_		-	1.0E+04	_
Nitrobenzene	0	_	_	1.7E+01	6.9E+02	_		1.7E+01	6.9E+02		_	_		_	_	_			_	1.7E+01	6.9E+02
N-Nitrosodimethylamine ^C	0			6.9E-03	3.0E+01			6.9E-03	3.0E+01		_	_	_		_		_		-	6.9E-03	3.0E+01
N-Nitrosodiphenylamine ^C	0			3.3E+01	6.0E+01	_	_	3.3E+01	6.0E+01				_	_	_	_	-]			
N-Nitrosodi-n-propytamine ^C	0	_	_	5.0E-02	5.1E+00		-	5.0E-02	5.1E+00	_	_		_	"	_	_	••	-	_	3.3E+01	6.0E+01
1	0.0	2.BE+01	6.6E+00	J.UL-02	V. 1E-100	2.8E+01	6 65 100	J.UE-02	J. 16 FOO	_	7	*-		_	_	-	-			5.0E-02	5.1E+00
Nonylphenol	1. 19 10 3000			_	_		6.6E+00	•	-	-	-	-	_	_	-		-	2.8E+01	6.6E+00	-	
Parathion	3 0	6.5E-02	1.3E-02		245.51	6.5E-02	1.3E-02	-	-	-			-	_	-	-		6.5E-02	1.3E-02	-	
PCB Total ^C	○ - 2 0 !		1.4E-02	6.4E-04	6.4E-04		1.4E-02	6.4E-04	6.4E-04				_	-		-	-	-	1.4E-02	6.4E-04	6.4E-04
Pentachiorophenol ^c	0"	5.8E+00	4.5E+00	2.7E+00	3.0E+01	5.8E+00	4.5E+00	2.7E+00	3.0E+01	-	-	-	-	-	-	-	-	5.8E+00	4.5E+00	2.7E+00	3.0E+01
Phenol	0	-	-	1.0E+04	8.6E+05	-	-	1.0E+04	8.6E+05	-	-	-		-		-	-		_	1.0E+04	8.6E+05
Pyrene	Ô	_	-	8.3E+02	4.0E+03	-	-	8.3E+02	4.0E+03	-	-	**	-	-	-		-		-	8.3E+02	4.0E+03
Radionuclides	0		-	-	-	-	-	-			-	_		-		-		-	-		
Gross Atpha Activity (pCi/L)	0	_		1 5E±01	_	_		1.50±04													
Beta and Photon Activity	5 A	_		1.5E+01	_	-		1.5E+01		_	-	-		"	-	-			-	1.5E+01	-
(mrem/yr)	0	-	-	4.0E+00	4.0E+00	-	-	4.0E+00	4.0E+00		••	-	_	-	_	_				4.0E+00	4.0E+00
Radium 226 + 228 (pCi/L)	0		_	5.0E+00	_	-	-	5.0E+00	-	_		-	_	-	_	-	_			5.0E+00	-
Uranium (ug/l)	О .			3.0E+01		-	_	3.0E+01	_		_	_		_		_	••	<u>-</u>			
											• • • • • • • • • • • • • • • • • • • •							<u> </u>		3.0E+01	

						T								,							· · · · · · · · · · · · · · · · · · ·
Parameter	Background		Water Qua	ality Criteria			Wasteload	1 Allocations	· · · · · · · · · · · · · · · · · · ·		Antidegrada	tion Baseline		ΑΑ	ntidegradati	on Allocations			Most Limiti	ng Allocations	4
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	HH	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НH	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн
Selenium, Total Recoverable	0.00	2.0E+01	5.0E+00	1.7E+02	4.2E+03	2.0E+01	5.0E+00	1.7E+02	4.2E+03		_							2.0E+01	5.0E+00	1.7E+02	4.2E+03
Sitver .	0	6.9E+00		••	_	6.9E+00	-	-	-	-	_	••	_	_	_	_	-	6.9E+00			
Sulfate	0	-	-	2.5E+05	_			2.5E+05		~-	_		_	-	_	_	_	_		2.5E+05	
1,1,2,2-Tetrachloroethane ^c	<u> </u>	••	-	1.7E+00	4.0E+01	-	-	1.7E+00	4.DE+01	-		_	-	-	_	-			_	1.7E+00	4.0E+01
Tetrachioroethylene ^C	³ - 0 ∴ \$	_	-	6.9E+00	3.3E+01	-	-	6.9E+00	3.3E+01	_			-	_	_				_	6.9E+00	3.3E+01
Thallium	0	-	·	2.4E-01	4.7E-01	-		2.4E-01	4.7E-01	_		_	_	-		_		_	- ,	2.4E-01	4.7E-01
Toluene	0	-	-	5.1E+02	6.0E+03	·		5.1E+02	6.0É+D3		-	-	_	-			_		••	5.1E+02	6.0E+03
Total dissolved solids	, o =	-	-	5.0E+05	-		-	5.0E+05	- 1	-	-		-	-	-	_		-	_	5.0E+05	
Toxaphene ^C	0	7.3E-01	2.0E-04	2.8E-03	2.8E-03	7.3E-01	2.0E-04	2.8E-03	2.8E-03	-		-		-	-			7.3E-01	2.0E-04	2.8E-03	2.8E-03
Tributyltin	0	4.6E-01	7.2E-02		-	4.6E-01	7.2E-02			-			-	-	_			4.6E-01	7.2E-02		
1,2,4-Trichlorobenzene	0	-	-	3.5E+01	7.0E+01	-		3.5E+01	7.0E+01	-	-	-		-		_	_	-		3.5E+01	7.0E+01
1,1,2-Trichloroethane ^c	0	-		5.9E+00	1.6E+02	-	_	5.9E+00	1.6E+02	-	**	_		-	_					5.9E+00	1.6E+02
Trichloroethylene ^C	0 -		-	2.5E+01	3.0E+02	_	-	2.5E+01	3.0E+02	_		••	_	-	-					2.5E+01	3.0E+02
2,4,6-Trichlorophenol ^C	0	-	-	1.4E+01	2.4E+01			1.45+01	2.4E+01		_	-	-		-		_		_	1.4E+01	2.4E+01
2-(2,4,5-Trichlorophenoxy) propionic acid (Silvex)	0	_		5.0E+01				5.0E+01	_			•••		_	_	_	_			£ 05+04	
Vinyl Chloride ^C	i	_	_	2.5E-01	2.4E+01	_	_	2.5E-01	2.4E+01	_	_		_	_	_	-	_		••	5.0E+01	
1	ss=_*	4.75.00	4.75.00			4.75.00	4.75.00				_	~		_	_	-			-	2.5E-01	2.4E+01
Zinc ·	# · 0	1.7E+02	1.7E+02	7.4E+03	2.6E+04	1.7E+02	1.7E+02	7.4E+03	2.6E+04									1.7E+02	1.7E+02	7.4E+03	2.6E+04

Notes:

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise
- 2. Discharge flow is highest monthly average or Form 2C maximum for Industries and design flow for Municipals
- 3. Metals measured as Dissolved, unless specified otherwise
- 4. "C" indicates a carcinogenic parameter
- Regular WLAs are mass balances (minus background concentration) using the % of stream flow entered above under Mixing Information.
 Antidegradation WLAs are based upon a complete mix.
- 6. Antideg. Baseline = (0.25(WQC background conc.) + background conc.) for acute and chronic
 - = (0.1(WQC background conc.) + background conc.) for human health
- 7. WLAs established at the following stream flows: 1Q10 for Acute, 30Q10 for Chronic Ammonia, 7Q10 for Other Chronic, 30Q5 for Non-carcinogens and Harmonic Mean for Carcinogens. To apply mixing ratios from a model set the stream flow equal to (mixing ratio 1), effluent flow equal to 1 and 100% mix.

		_
Metal	Target Value (SSTV)	Note: do not use QL's lower than the
Antimony	5.6E+00	minimum QL's provided in agency
Arsenic	1.0E+01	guidance
Barium	2.0E+03	
Cadmium	9.4E-01	
Chromium III	6.2E+01	
Chromium VI	6.4E+00	
Capper	7.6E+00	
Iron	3.0E+02	
Lead	1.4E+01	
Manganese	5.0E+01	
Mercury	4.6E-01	
Nickel	1.7E+01	
Selenium	3.0E+00	
Silver	2.8E+00	
Zinc	6.6E+01	

FRESHWATER WATER QUALITY CRITERIA / WASTELOAD ALLOCATION ANALYSIS

Facility Name:

Lucketts Elementary

Permit No.: VA0021750

Receiving Stream:

Early Life Stages Present Y/N? =

Limestone Branch, UT

Version: OWP Guidance Memo 00-2011 (8/24/00)

Stream Information		Stream Flows	Mixing Information	Effluent Information	_
Mean Hardness (as CaCO3) =	mg/L	1Q10 (Annual) = 0 MGD	Annual - 1Q10 Mix = %	Mean Hardness (as CaCO3) =	150 mg/L
90% Temperature (Annual) =	deg C	7Q10 (Annual) = 0 MGD	- 7Q10 Mix = %	90% Temp (Annual) =	25 deg C
90% Temperature (Wet season) =	ि ेे deg C	30Q10 (Annual) = 01MGD	- 30Q10 Mix = %	90% Temp (Wet season) =	15 deg C
90% Maximum pH =	, SU	1Q10 (Wet season) = 0 MGD	Wet Season - 1Q10 Mix = %	90% Maximum pH =	7 SU
10% Maximum pH =	ja ja ja su	30Q10 (Wet season)	- 30Q10 Mix = % %	10% Maximum pH =	6.6 SU
Tier Designation (1 or 2) =		30Q5 = 0 MGD		Discharge Flow =	0.01175 MGD
Public Water Supply (PWS) Y/N? =	y.	Harmonic Mean = 0 MGD		-	,
Trout Present Y/N? =	in in				

Parameter	Background		Water Qua	lity Criteria			Wasteload	1 Allocations			Antidegrada	tion Baseline		<u> </u>	ınlidegradati	ion Allocations			Most Limit	ing Allocations	S
(ug/t untess noted)	Conc.	Acute	Chronic	HH (PWS)	HH	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН
Acenapthene	9 0	-	-	6.7E+02	9.9E+02		_	6.7E+02	9.9E+02	· -	-	_	_		_		-	_		6.7E+02	9.9E+02
Acrolein	0	_		6.1E+00	9.3E+00	_	-	6.1E+00	9.3E+00	_	_			-	_	•	_		_	6.1E+00	9.3E+00
Acrylonitrile ^c	5. 0/.0		-	5.1E-01	2.5E+00	-	-	5.1E-01	2.5E+00	_	••	_	_	_		_		_	_	6.1E-01	2.5E+0D
Aldrin ^c	0	3.0E+00	-	4.9E-04	5.0E-04	3.0E+00	_	4.9E-04	5.0E-04		_	_	-		_		_	3.0E+00		4.9E-04	5.0E-04
Ammonia-N (mg/l)					•					:											0.02 04
(Yearly) Ammonia-N (mg/l)	0	3.61E+01	3.01E+00	_	_	3.61E+01	3.01E+00	**		_		-	-	-		-	_	3.61E+01	3.01E+00	-	••
(High Flow)	1. 0 3 m	3.61E+01	5.73E+00	-	_	3.61E+01	5.73E+00	_	_		**	· _	-	_	_	_	_	3.61E+01	5.73E+00	-	
Anthracene	. 0	_	-	8.3E+03	4.0E+04	_		8.3E+03	4.0E+04	-	-	-	_	-			_			8.3E+03	4.0E+04
Antimony	0	_		5.6E+00	6.4E+02	-	_	5.6E+00	6.4E+02	-	_		_	_	_	_			_	5.6E+00	6.4E+02
Arsenic	.0.	3.4E+02	1.5E+02	1.0E+01	_	3.4E+02	1.5E+02	1.0E+01	_			_	_		_		-	3.4E+02	1.6E+02	1.0E+01	-
Barium	. 0	_		2.0E+03	_	_		2.0E+03		-	_	_	_		_	_				2.0E+03	
Benzene ^c	0	_	_	2.2E+01	5.1E+02		_	2.2E+01	5.1E+02	_	-	_		_	_		_		_	2.2E+01	5.1E+02
Benzidine ^C			_	8.6E-04	2.0E-03	_	-	8.6E-04	2.0E-03	-	_			_		_	_		-	8.6E-04	2.0E-03
Benzo (a) anthracene ^c	0	_		3.8E-02	1.8E-01		-	3.8E-02	1.8E-01	_	_	-	_	_	_	_	_		-	3.8E-02	1.8E-01
Benzo (b) fluoranthene ^c	0	_	_	3.8E-02	1.8E-01	_	_	3.8E-02	1.8E-01	_		_	_			_	_	"	-	3.8E-02	
Benzo (k) fluoranthene ^c		_	_	3.8E-02	1.8E-01	_	_	3.8E-02	1.8E-01	_	_	_	_		_	_	-	-	-		1.8E-01
Benzo (a) pyrene ^c	0			3.8E-02	1.8E-01		_	3.8E-02	1.8E-01	_	_		_		_	-	_	-	~	3.8E-02	1.8E-01
Bis2-Chloroethyl Ether C	0.	-	_	3.0E-01	5.3E+00		-	3.0E-01	5.3E+00	_	_	_	_	_	_	_	**	-	-	3.8E-02	1.8E-01
Bis2-Chloroisopropyl Ether	0		_	1.4E+03	6.5E+04	_	-	1.4E+03	6.5E+04	_	_	_	_		_	-	_	_	-	3.0E-01	5.3E+00
Bis 2-Ethylhexyl Phthalate C	Ó	-	_	1.2E+01	2.2E+01	_	_	1.2E+01	2.2E+01	-	_	_	-	_	-	-	_	_	•	1.4E+03	6.5E+04
Bromoform ^C	0 0		_	4.3E+01	1.4E+03	_		4.3E+01	1.4E+03	_	_	-	-	_	-	-	-	_	-	1.2E+01	2.2E+01
Butylbenzylphthalate	0	_		1.5E+03	1.9E+03	_	_	1.5E+03				_	_	_	_	- '	-	-	-	4.3E+01	1.4E+03
➤ imium	0	6.2E+00	1.6E+00	5.0E+00	1.92+03	6.2E+00	1.6E+00	5.0E+00	1.9E+03	_	-	-	_		-	-	**	_	-	1.5E+03	1.9E+03
	0				1.6E+01	1			4.05.54	_	-		-	-	-	-	-	6.2E+00	1.6E+00	5.0E+00	-
bon Tetrachloride ^c		2.45400	4 25 02	2.3E+00		245.00	- ,	2.3E+00	1.6E+01	-	_			_	-	-		-	-	2.3E+00	1.6E+01
	0,5	2.4E+00	4.3E-03	8.0E-03	8.1E-03	2.4E+00	4.3E-03	8.0E-03	8.1E-03	-	-	-	-	_	-	-	-	2.4E+00	4.3E-03	8.0E-03	8.1E-03
ride	0	8.6E+05	2.3E+05	2.5E+05		8.6E+05	2.3E+05	2.5E+05	-	-	-	-	-	-	.=		-	8.6E+05	2.3E+05	2.6E+05	-
⊕	0	1.9E+01	1.1E+01		_	1.9E+01	1.1E+01		-	-	-		-	-	•	-	-	1.9E+01	1.1E+01		-
robenzene	0		· -	1.3E+02	1.6E+03	<u> </u>		1.3E+02	1.6E+03		-	•	-	-	-		-		_	1.3E+02	1.6E+03

~1

Parameter	Background	Background Water Quality Criteria				Г	Wastelga	d Allocations			Antidegradation	Pacelino		Τ ,				1			
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН	Acute	T I		ш		1	tion Allocations		 		ng Allocation	
Chlorodibromomethane ^C	50000			4.0E+00	1.3E+02	7,0010	T CHICHE	4.0E+00	1.3E+02		Chronic LHH	(PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН
Chloraform	o. S		••	3.4E+02	1.1E+04	_	_	3.4E+02	1.1E+D4	-	_	~		_	_	-	-	-		4.0E+00	1.3E+02
2-Chioronaphthalene		_		1.0E+03	1.6E+03		_	1.0E+03	1.6E+03	_		_	_	_	••	-	-	-	-	3.4E+02	1.1E+04
2-Chlorophenol	0.5	_	_	8.1E+01	1.5E+02	_				_		-	_	_	-	-	-	-	-	1.0E+03	1.6E+03
Chlorpyrifos	0 -	8.3E-02	4.1E-02	0.12.01		9 35 03	445.00	8.1E+01	1.5E+02	_	-		-	-	-			-	-	8.1E+01	1.5E+02
Chromium III	0 1	7.9E+02		-	-	8.3E-02	4.1E-02	-		-	_	_		-	_		-	8.3E-02	4.1E-02	••	-
			1.0E+02	_	_	7.9E+02	1.0E+02	-		_		_		_	-	-		7.9E+02	1.0E+02	••	-
Chromium VI	0	1.6E+01	1.1E+01	4.05.00	-	1.6E+01	1.1E+01	-			**	_	-	_		-		1.6E+01	1.1E+01	-	
Chromium, Total Chrysene ^c	5 · · · · · · · · · · · · · · · · · · ·	_		1.0E+02	4.05.00	-	-	1.0E+02		_	_	-	-	-	-	-		-	-	1.0E+02	••
	国际发生的		4.05.04	3.8E-03	1.8E-02			3.8E-03	1.8E-02	-	_	-	-	-	-	-	-		-	3.8E-03	1.8E-02
Copper	0	2.0E+01	1,3E+01	1.3E+03	4.05.04	2.0E+01	1.3E+01	1.3E+03	- -	-		_	-	-	_		-	2.0E+01	1.3E+01	1.3E+03	-
Cyanide, Free DDD ^C		2.2E+01	5.2E+00	1.4E+02	1.6E+04	2.2E+01	5.2E+00	1.4E+02	1.6E+04		_		-			••	-	2.2E+01	5.2E+00	1.4E+02	1.6E+04
DDE C	, ° %	_	7	3.1E-03	3.1E-03	-	-	3.1E-03	3.1E-03	-	-	-	-	-		-	-	-	-	3.1E-03	3.1E-03
DDT °	. 0	4.5.00		2.2E-03	2.2E-03		-	2.2E-03	2.2E-03	-	••	_	-	~		-		-	-	2.2E-03	2.2E-03
	0	1.1E+00	1.0E-03	2.2E-03	2.2E-03	1.1E+00	1.0E-03	2.2E-03	2.2E-03	_	-	-		-	-		_	1.1E+00	1.0E-03	2.2E-03	2.2E-03
Demeton	1 000	_	1.0E-01	-	_	-	1.0E-01	-	-	-	 '	-	-	-		- ·	-	-	1.0E-01		
Diazinon	1993	1.7E-01	1.7E-01	••	-	1.7E-01	1.7E-01	-	-	-		_	-	-	_	-	_	1.7E-01	1.7E-01	••	
Dibenz(a,h)anthracene ^c	0 😅	-	_	3.8E-02	1.8E-01	-	-	3.8E-02	1.8E-01	_	-		-	-	-	~	-	-		3.8E-02	1.8E-01
1,2-Dichlorobenzene	0	_	-	4.2E+02	1.3E+03		-	4.2E+02	1.3E+03	-	-		-	-			_	-	-	4.2E+02	1.3E+03
1,3-Dichlorobenzene	. 0	-	-	3.2E+02	9.6E+02	-	-	.3.2E+02	9.6E+02	-		-	-		_	-	-		-	3.2E+02	9.6E+02
1,4-Dichlorobenzene	0 4	-	. –	6.3E+01	1.9E+02	-	••	6.3E+01	1.9E+02	-	-	-		-	_		-	-		6.3E+01	1.9E+02
3,3-Dichlorobenzidine ^c	0	-	-	2.1E-01	2.8E-01	-		2.1E-01	2.8E-01	-		-		-	_	_				2.1E-01	2.8E-01
Dichlorobromomethane ^C	0.7			5.5E+00	1.7E+02		-	5.5E+00	1.7E+02	-	-		-	-		-	_			5.5E+00	1.7E+02
1,2-Dichloroethane ^c	0			3.8E+00	3.7E+02	-	-	3.8E+00	3.7E+02		-	-		-		-	**	-		3.8E+00	3.7E+02
1,1-Dichloroethylene		-	-	3.3E+02	7.1E+03	-	-	3.3E+02	7.1E+03	-	_			-	-	-	_	-		3.3E+02	7.1E+03
1,2-trans-dichloroethylene	0			1.4E+02	1.0E+04	-		1.4E+02	1.0E+04		-		-	-		-	**			1.4E+02	1.0E+04
2,4-Dichlorophenol	. 0	-	-	7.7E+01	2.9E+02		-	7.7E+01	2.9E+02	-	_		- i		-	-	_	_		7.7E+01	2.9E+02
2,4-Dichlorophenoxy acetic acid (2,4-D)	0	_	_	1.0E+02	_			1.0E+02	_					_			_			1.0E+02	
1,2-Dichioropropane ^C	0	-	_	5.0E+00	1.5E+02	_	_	5.0E+00	1.5E+02	_		_	_		_		_				4.65100
1,3-Dichloropropene ^c	0		_	3.4E+00	2.1E+02			3.4E+00	2.1E+02		_		_	_	-	_			_	5.0E+00 3.4E+00	1.6E+02
Dieldrin ^C	0	2.4E-01	5.6E-02	5.2E-04	5.4E-04	2.4E-01	5.6E-02	5.2E-04	5.4E-04	_	_		_	_	_	_	_	2.4E-01	5.6E-02		2.1E+02
Diethyl Phthalate	0	_		1.7E+04	4.4E+04	_	_	1.7E+04	4.4E+04	-			_	_			_	2.42-01	5.00-02	5.2E-04	5.4E-04
2,4-Dimethylphenol	0	_	_	3.8E+02	8.5E+02			3.8E+02	8.5E+02	_	_	_	_	_	_	_			-	1.7E+04	4.4E+04
Dimethyl Phthalate	0	_	_	2.7E+05	1.1E+06	_		2.7E+05	1.1E+06	_	_		_	_	_	_	_		_	3.8E+02	8.5E+02
Di-n-Butyl Phthalate	0		_	2.0E+03	4.5E+03	_	_	2.0E+03	4.5E+03	**			_	_	-	_	_		-	2.7E+05	1.1E+06
2,4 Dinitrophenol	0			6.9E+01	5.3E+03		_	6.9E+01	5.3E+03	~		••	_	_		-	_			2.0E+03	4.5E+03
2-Methyl-4,6-Dinitrophenol	0	_	_	1.3E+01	2.8E+02	_	_	1.3E+01	2.8E+02			_	_			_	_		-	6.9E+01	5.3E+03
2,4-Dinitrototuene ^C	0		_	1.1E+00	3.4E+01			1.1E+00	3.4E+01	_	_		_	_	_			-	-	1.3E+01	2.8E+02
Dioxin 2,3,7,8-					2			,	3.15.01	- -				-	_	~			•	1.1E+00	3.4E+01
tetrachlorodibenzo-p-dioxin	0	-	-	5.0E-08	5.1E-08	-	-	5.DE-08	5.1E-08		- '	-		_	_				-	5.0E-08	5.1E-08
1,2-Diphenylhydrazine ^c	0	-	-	3.6E-01	2.0E+00		-	3.6E-01	2.0E+00	-	-			_	-	-	-			3.6E-01	2.0E+00
Alpha-Endosulfan	0	2.2E-01	5.6E-02	6.2E+01	8.9E+01	2.2E-01	5.6E-02	6.2E+01	8.9E+01			_	-			-		2.2E-01	5.6E-02	6.2E+01	8.9E+01
Beta-Endosulfan	0 ,	2.2E-01	5.6E-02	6.2E+01	8.9E+01	2.2E-01	5.6E-02	6.2E+01	8.9E+01	-		-	-	_	-	-	-	2.2E-01	5.6E-02	6.2E+01	8.9E+01
Alpha + Beta Endosulfan	70	2.2E-01	5.6E-02		-	2.2E-01	5.6E-02	-	-	-			-	-	-	_	-	2.2E-01	5.6E-02		
Endosulfan Sulfate	0	-	-	6.2E+01	8.9E+01	-	••	6.2E+01	8.9E+01	-		-	-	-						6.2E+01	8.9E+01
Endrin	0	8.6E-02	3.6E-02	5.9E-02	6.0E-02	8.6E-02	3.6E-02	5.9E-02	6.0E-02	-		••	-		-	-	-	8.6E-02	3.6E-02	5.9E-02	6.0E-02
Endrin Aldehyde	0 -			2.9E-01	3.0E-01		-	2.9€-01	3.0E-01		 .	_	- 1	_		••	_	-	_	2.9E-01	3.0E-01

Parameter	Background		Water Qua	ality Criteria			Wasteload	Allocations			Antidegrada	tion Baseline		A	ntidegradatio	n Allocations			Most Limiti	ng Allocations	
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН
Ethylpenzene	0	-		5.3E+02	2.1E+03	_	-	5.3E+02	2.1E+03	_	-					_	_			5.3E+02	2.1E+03
Fluoranthene	0	-	-	1.3E+02	1.4E+02		_	1.3E+02	1.4E+02					_	_					1.3E+02	1.4E+02
Fluorene	0.	-	**	1.1E+03	5.3E+03	-	_	1.1E+03	5.3E+03					-	_	**			_	1.1E+03	5.3E+03
Foaming Agents	, O	-		5.0E+02		_	_	5.0E+02	-		_	_	_	Ì	_	~*			_	5.0E+02	
Guthion	o de		1.0E-02	_	-		1.0E-02		_	_	_		_	_				_	1.0E-02		
Heptachlor ^c	. 0	5.2E-01	. 3.8E-03	7.9E-04	7.9E-04	5.2E-01	3.8E-03	7.9E-04	7.9E-04		_	_		-	-		_	5.2E-01	3.8E-03	7.9E-04	7.9E-04
Heptachlor Epoxide ^C	, o-	5.2E-01	3.8E-03	3.9E-04	3.9E-04	5.2E-01	3.8E-03	3.9E-04	3.9E-04	_	_	_	_	_	_	·		5.2E-01	3.8E-03	3.9E-04	3.9E-04
Hexachlorobenzene ^C	0	_	· _	2.8E-03	2.9E-03		_	2.8E-03	2.9E-03	_		_		-		_	_			2.8E-03	2.9E-03
Hexachlorobuladiene ^C	8 O		_	4.4E+00	1.8E+02			4.4E+00	1.8E+02			_			~	_				4.4E+00	1.8E+02
Hexachlorocyclohexane	學有主義的					l															
Alpha-BHC ^c	· ``o · · · · · ·	- '	_	2.6E-02	4.9E-02	-		2.6E-02	4.9E-02	-	-			-	-	-	-			2.6E-02	4.9E-02
Hexachlorocyclohexane Beta-BHC ^C																					
Hexachlorocyclohexane	0 3	-	-	9.1E-02	1.7E-01	_	_	9,1E-02	1.7E-01	-	_	-	_		-	-			٦.	9.1E-02	1.7E-01
Gamma-BHC ^C (Lindane)	0	9.5E-01	_	9.8E-01	1.8E+00	9.5E-01	_	9.8E-01	1.8E+00	_	_	_		_	<u>-</u>		_	9.5E-01		9.8E-01	1.8E+00
Hexachtorocyclopentadiene	0	_	· _	4.0E+01	1.1E+03	_	_	4.0E+01	1.1E+03	_		_	~		_				_	4.0E+01	1.1E+03
Hexachtoroethane ^C		_	_	1.4E+01	3.3E+01	_	_	1.4E+01	3.3E+01	_	_	_		۱	_	_	_		_	1.4E+01	3.3E+01
Hydrogen Sulfide	D.	_	2.0E+00	_	_	_	2.0E+00	_	_	_	_	_	_	_	_		_		2.0E+00		0,52,01
Indeno (1,2,3-cd) pyrene ^C	0		2.02.700	3.8E-02	1.8E-01	_	2.02.00	3,8E-02	1.8E-01	_			_	_	_			_	2.00,100	3.8E-02	1.8E-01
Iron	p		_	3.0E+02	-	_	_	3.0E+02			_	_	_	_	_				-		1.55-01
Isophorone ^c	0			3.5E+02	9.6E+03		_	3.5E+02	9.6E+03	_		_	_	_	_	_	_			3,0E+02	0.05.03
	0	_	0.0E+00	3.5E+02	B.0E+03	I -	0.0E+00	3.3E+02	8.0E+03	_	_	_		_	-	-	_	_	-	3.5E+02	9.6E+03
Kepone		205100		4 65+04	-	2.05+02		1.5E+01	-	-	•			_		-		2.05.02	0.0E+00	4.55.64	••
Lead	0	2.0E+02	2.3E+01	1.5E+01	_	2.0E+02	2.3E+01	1.56+01	-	-			-	~		-	-	2.0E+02	2.3E+01	1.5E+01	-
Malathion	0	_	1.0E-01	5.05+04	-	_	1.0E-01	- 6.05.04	-	-		-		-	-	-	-	-	1.0E-01	 	-
Manganese	0	45.00	7 75 04	5.0E+01	-	45.00	7.75.04	5.0E+01		_		_	-			-	_	4.5.00		6.0E+01	••
Mercury	0	1.4E+00	7.7E-01	4.75.64	4.55.88	1.4E+00	7.7E-01	4 75 . 04	4.55.00	-	**		-	-	-	_	_	1.4E+00	7.7E-01		
Methyl Bromide Methylene Chloride ^C	0	-	_	4.7E+01	1.5E+03	_	_	4.7E+01	1.5E+03	_	_	-	_	"	**	-	-	_	-	4.7E+01	1.5E+03
	D	_		4.6E+01	5.9E+03	_	-	4.6E+01	5.9E+03	-		-		_	-	-	-	-		4.6E+01	5.9E+03
Methoxychlor	0	_	3.0E-02	1.0E+02	-	_	3.0E-02	1.0E+02		-	-	-	-	-	-	-		-	3.0E-02	1.0E+02	-
Mirex	0		0.0E+00				0.0E+00			_	-	_	_	_	-	-	-	-	0.0E+00	-	••
Nickel	0	2.6E+02	2.9E+01	6.1E+02	4.6E+03	2.6E+02	2.9E+01	6.1E+02	4.6E+03	-		-	-	-	-		_	2.6E+02	2.9E+01	6.1E+02	4.6E+03
Nitrate (as N)	0	-	-	1.0E+04			-	1.0E+04		-	-	-	-	-	-	-	-			1.0E+04	
Nitrobenzene	0	-	-	1.7E+01	6.9€+02			1.7E+01	6.9E+02	-	-		-	-	-	-	-	-		1.7E+01	6.9E+02
N-Nitrosodimethylamine ^C	.0		-	6.9E-03	3.0E+01		-	6.9E-03	3.0E+01		••		-	-	-	-	-	**		6.9E-03	3.0E+01
N-Nitrosodiphenytamine ^c	0	-	-	3.3E+01	6.0E+01	-	_	3.3E+01	6.0E+01	-	-	-	-	-	-	-	-	-	-	3.3E+01	6.0E+01
N-Nitrosodi-n-propylamine	0.	-	-	5.0E-02	5.1E+00	-		5.0E-02	5.1E+00		••		-		-				-	5.0E-02	6.1E+00
Nonyiphenol	0	2.8E+01	6.6E+00			2.8E+01	6.6E+00	-	-	-	-	-	-	-		-	-	2.8E+01	6.6E+00		-
Parathion	0	6.5E-02	1,3E-02	-	-	6.5E-02	1.3E-02	-	-	-	-	-	-	-	-	-		6.5E-02	1.3E-02		_
PCB Total ^C	10° 10° 10° 10° 10° 10° 10° 10° 10° 10°		1.4E-02	6.4E-04	6.4E-04	-	1.4E-02	6.4E-04	6.4E-04	-	-	-	-	-	-				1.4E-02	6.4E-04	6.4E-04
Pentachlorophenol ^c	0	5.8E+00	4.5E+00	2.7E+00	3.0E+01	5.8E+00	4.5E+00	2.7E+00	3.0E+01	-		 .		-		-	-	5.8E+00	4.5E+00	2.7E+00	3.0E+01
Phenol	0	-	-	1.0E+04	8.6E+05	-	-	1.0E+04	8.6E+05	-	-			-		-		-	-	1.0E+04	8.6E+05
Pyrene	5 0	-		8.3E+02	4.0E+03	_		8.3E+02	4.0E+03	_	-	-	-	-	-	_	-	-	~	8.3E+02	4.0E+03
Radionuclides	0.		-	-		-	-	-			-	-	-	-		-		-	-		-
Gross Alpha Activity (pCi/L)	0	_	- <u></u>	1.5E+01	_	_	_	1.5E+01	_	_	_		_	_						4 55:04	
Beta and Photon Activity	The state of the state of	-	_		_	_	_	1.02.01	-	_	_				-	-	-	-		1.5E+01	-
(mrem/yr)	Ò.			4.0E+00	4.0E+00	-	-	4.0E+00	4.0E+00	-	-			-	-		_	-	-	4.0E+00	4.0E+00
Radium 226 + 228 (pCl/L)	Ö	-	-	5.0E+00		-		5.0E+00	- 1					-	-		-		-	5.0E+00	
Uranium (ug/l)	A 0 🚉	<u> </u>		3.0E+01	~			3.0E+01		-	_						-	_		3.0E+01	

Parameter	Background		Water Qua	ality Criteria			Wasteload	d Allocations			Antidegrada	ation Baseline		A	ntidegradati	ion Allocations			Most Limiti	ng Allocations	
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	нн	Acute	Chronic	T	нн	Acute	Chronic	HH (PWS)	НН
Selenium, Total Recoverable	0 1	2.0E+01	5.0E+00	1.7E+02	4.2E+03	2.0E+01	5.0E+00	1.7E+02	4.2E+03	_		_				-		2.0E+01	5.0E+00	1.7E+02	4.2E+03
Silver	F 0 5	6.9E+00		<u>-</u>	_	6.9E+00	-	-		_		_			_			6.9E+00	_		
Sulfate	0		-	2.5E+05		-	_	2.5E+05	_		_	_	~-		_			_	_	2.5E+05	
1,1,2,2-Tetrachloroethane ^C	. O .	_	-	1.7E+00	4.0E+01	-		1.7E+00	4.0E+01	_	_			_			_	.	_	1.7E+00	4.0E+01
Tetrachloroethylene ^c	. ×∵ o	-		6.9E+00	3.3E+01	-	_	6.9E+00	3.3E+01	_	_	_		_		_				6.9E+00	3.3E+01
Thallium	5 o 5	-	~	2.4E-01	4.7E-01		_	2.4E-01	4.7E-01			_		_	_	_	_			2.4E-01	4.7E-01
Toluene	o l			5.1E+02	6.0E+03		_	5.1E+02	6.0E+03						_	_			-	5.1E+02	6.0E+03
Total dissolved solids	0 1	_	_	5.0E+05			_	5.DE+05	_	_	_		_	١	_					5.0E+05	
Toxaphene ^C	0	7.3E-01	2.0E-04	2.8E-03	2.8E-03	7.3E-01	2.0E-04	2.8E-03	2.8E-03	_		_		"	_	_	_	7.3E-01	2.0E-04	2.8E-03	
Tributyltin	0	4.6E-01	7.2E-02	_	-	4,6E-01	7.2E-02		2.02-00	_	_		_	-	_	_		4.6E-01	7.2E-02	2.0E-U3	2.8E-03
1,2,4-Trichlorobenzene	0 .			3.5E+01	7.0E+01	1.02-01	,. <u></u>	3.5E+01	7.0E+01				_	-	_	-	_	4.05-01	1.2E-02		7.45.44
1,1,2-Trichloroethane ^C		_	_	5.9E+00	1.6E+02			5.9E+00	1.6E+02	_		-	_	-	-	-	_	_		3,5E+01	7.0E+01
Trichloroethylene C	0	_		2.5E+01	3.0E+02	_	_	2.5E+01	3.0E+02	-	-	_	-	-	_	-	-	_	-	5.9E+00	1.6E+02
2,4,6-Trichlarophenol ^c	0			1.4E+01		_			i		-	••	-	-	-	-	-	_	-	2.5E+01	3.0E+02
2-(2,4,5-Trichlarophenoxy)		-	-	1.46701	2.4E+01	_	-	1.4E+01	2.4E+01	-	-		-	_	-	-		-		1.4E+01	2.4E+01
propionic acid (Silvex)	0		-	5.0E+01		-	-	5.0E+01				_		-	-		-	-		5.0E+01	
Vinyl Chloride ^C	0			2.5E-01	2.4E+01	-	-	2.5E-01	2.4E+01	-	-	••	-			_		-	_	2.6E-01	2.4E+01
Zinc	° 0	1.7E+02	1.7E+02	7.4E+03	2.6E+04	1.7E+02	1.7E+02	7.4E+03	2.6E+04	-	-				_			1.7E+02	1.7E+02	7.4E+03	2.6E+04

Notes:

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise
- 2. Discharge flow is highest monthly average or Form 2C maximum for Industries and design flow for Municipals
- 3. Metals measured as Dissolved, unless specified otherwise
- 4. "C" indicates a carcinogenic parameter
- Regular WLAs are mass balances (minus background concentration) using the % of stream flow entered above under Mixing Information. Antidegradation WLAs are based upon a complete mix.
- 6. Antideg. Baseline = (0.25(WQC background conc.) + background conc.) for acute and chronic
 - = (0.1(WQC background conc.) + background conc.) for human health
- 7. WLAs established at the following stream flows: 1Q10 for Acute, 30Q10 for Chronic Ammonia, 7Q10 for Other Chronic, 30Q5 for Non-carcinogens and Harmonic Mean for Carcinogens. To apply mixing ratios from a model set the stream flow equal to (mixing ratio 1), effluent flow equal to 1 and 100% mix.

Metal	Target Value (SSTV)],
Antimony	5.6E+00	٦,
Arsenic	1.0E+01	ļ
Barlum	2.0E+03	1
Cadmium	9.4E-01	l
Chromium III	6.2E+01	l
Chromium VI	6.4E+00	l
Copper	7.6E+00	l
Iron	3.0E+02	ļ
Lead	1.4E+01	İ
Manganese	5.0E+01	ı
Mercury	4.6E-01	ı
Nickel	1.7E+01	ı
Selenium	3.0E+00	
Silver	2.8E+00	ı
Zinc	6.6E+01	1

Note: do not use QL's lower than the minimum QL's provided in agency guidance

Permit #:VA0021750 Facility Lucketts Elementary School

Rec'd	Parameter Description	QTY L	Lim .	QTY	Lim	Units	CONC	Lim	CONC	Lim	CONC	Lim	Units
				MAX	Max		MIN	Min	AVG	Ävg	MAX	Max	
09-Mar-2009	AMMONIA, AS N		*****	NULL	****	NULL	NULL	****	4.46	2.0	4.46	√ 20	MG/L
06-Apr-2009	AMMONIA, AS N		34484F	NULL	*****	NULL	NULL	*****	0.42		0.42		MG/L
08-May-2009	AMMONIA, AS N		*****	NULL	*****	NULL	NULL		<0.10		<0.10		MG/L
05-Jun-2009	AMMONIA, AS N		*****	NULL	*****	NULL	NULL		0.33	2:0	0.33		MG/L
06-Jul-2009	AMMONIA, AS N	*	****	NULL	*****	NULL	NULL		0.15	2.0	0.15	2.0	MG/L
07-Oct-2009	AMMONIA, AS N	NULL ****	****	NULL	******	NULL	NULL	, <u>.</u>	0.44	2.0	0.44	2.0	MG/L
05-Nov-2009	AMMONIA, AS N	NULL	*****	NULL	******	NULL	NULL	******	0.77	2.0	0.77	£ 2.0	MG/L
04-Dec-2009	AMMONIA, AS N	NULL ***	*****	NULL	*****	NULL	NULL	****	0.13	2.0	0.13	2.0	MG/L
08-Jan-2010	AMMONIA, AS N	NULL ****	*****	NULL	******	NULL	NULL	f*******	0.61	2.0	0.61	2.0	MG/L
04-Feb-2010	AMMONIA, AS N	NULL ****	*****	NULL	*****	NULL	NULL	*****	1.00	2.0	1.00	2.0	MG/L
08-Mar-2010	AMMONIA, AS N	NULL ****	****	NULL	****	NULL	NULL	*******	1.86	- 2.0	1.86	2.0	MG/L
09-Apr-2010	AMMONIA, AS N	NULL ****	****	NULL	*****	NULL	NULL	******	<1.16	2.0	2.21	2.0	MG/L
10-May-2010	AMMONIA, AS N	NULL ****	*****	NULL	*****	NULL	NULL	******	<0.10	2.0	<0.10	2.0	MG/L
04-Jun-2010	AMMONIA, AS N	NULL ****	****	NULL	*****	NULL	NULL	****	<0.10	2.0	<0.10		MG/L
07-Jul-2010	AMMONIA, AS N	NULL *****	*****	NULL	****	NULL	NULL	*****	<0.10	2.0	<0.10	2.0	MG/L
08-Oct-2010	AMMONIA, AS N	NULL ****	****	NULL	*****	NULL	NULL	1 2 2	<0.10	2.0	<0.10	2. 2.0	MG/L
09-Nov-2010	AMMONIA, AS N	NULL ***	*****	NULL	*****	NULL	NULL	******	<0.10	2.0	<0.10	4-	MG/L
06-Dec-2010	AMMONIA, AS N	NULL ****	****	NULL	****	NULL	NULL	*****	<0.10		<0.10	2.0	MG/L
07-Jan-2011	AMMONIA, AS N	NULL ****	*****	NULL	******	NULL	NULL	******	0.62	2.0	0.62	113-20 200	MG/L
03-Feb-2011	AMMONIA, AS N	NULL ****	****	NULL	*****	NULL	NULL	*****	<0.10	°× 2.0	<0.10		MG/L
07-Mar-2011	AMMONIA, AS N	NULL ***	*****	NULL	*****	NULL	NULL	******	<0.10	2.0	<0.10		ł
07-Apr-2011	AMMONIA, AS N		****	NULL	******	NULL	NULL	******	<0.10	2.0	<0.10	2.0	
04-May-2011	AMMONIA, AS N		*****	NULL	******	NULL	NULL	*****	<0.10	£ 2:0	<0.10	¹ ≠ 2.0	MG/L
06-Jun-2011	AMMONIA, AS N		*****	NULL	******	NULL	NULL	*****	<0.10	2.0	<0.10	3.1	
07-Jul-2011	AMMONIA, AS N		*****	NULL	******	NULL	NULL	*****	<0.10		<0.10		MG/L
03-Oct-2011	AMMONIA, AS N		RAWAR	NULL	*****	NULL	NULL	*****	<0.10	2.0	<0.10	2.0	MG/L
03-Nov-2011	AMMONIA, AS N	NULL	*****	NULL		NULL	NULL	******	<0.10	4.118.17.12.	<0.10	Prof. Align.	MG/L
06-Dec-2011	AMMONIA, AS N	NULL ****	****	NULL		NULL	NULL	*****	<0.10	2:0	<0.10	20	
09-Jan-2012	AMMONIA, AS N	NULL ****	****	NULL	*******	NULL	NULL	7.,	<0.10	2.0	<0.10	2.0	
06-Feb-2012	AMMONIA, AS N	NULL ****	****	NULL	******	NULL	NULL	*******	<0.10	2.0	<0.10	L + "K"	MG/L
08-Mar-2012	AMMONIA, AS N	NULL ****	*****	NULL		NULL	NULL	******	<0.10	2.0	<0.10		MG/L
09-Apr-2012	AMMONIA, AS N	NULL ****	CATA HARA	NULL		NULL	NULL	******	<0.10	2.0	<0.10		MG/L
03-May-2012	AMMONIA, AS N	NULL ****	****	NULL	******	NULL		******	<0.10	2.0	<0.10		MG/L
10-Jun-2012	AMMONIA, AS N	NIII I ****	****	NULL		NULL	NULL		<0.10	2.0	<0.10	200	MG/L
05-Jul-2012	AMMONIA, AS N		****	NULL	*****	NULL	NULL	*****	<0.10	2.0	<0.10	. 2.0	L
03-Oct-2012	AMMONIA, AS N	NULL ****	****	NULL	*****	NULL	NULL	*******	<0.10	2.0	<0.10	271	1
05-Nov-2012	AMMONIA, AS N	NULL ****	***	NULL	****	NULL		****	<0.10	2.0) - 2.0	L

06-Dec-2012	AMMONIA, AS N	NULL	*****	NULL	*******	NULL	NULL	******	<0.10	. 2.0	<0.10	. 2.0	М
04-Jan-2013	AMMONIA, AS N	NULL	******	NULL	*******	NULL	NULL	*****	<0.10		1	2.0	_
08-Feb-2013	AMMONIA, AS N		*****	NULL	*****		NULL	********	<0.10			2.0	_
05-Mar-2013	AMMONIA, AS N		*****	NULL	*****			*****	<0.10	- 2.0	<0.10		4
08-Apr-2013	AMMONIA, AS N	NULL	*****	NULL	*****	NULL		*****	<0.10	2.0	<0.10	20	М
08-May-2013	AMMONIA, AS N	NULL	*******	NULL	*******	NULL		******	<0.10	2.0	<0.10	r + 2.0	М
07-Jun-2013	AMMONIA, AS N	NULL	******	NULL	*****	1	NULL	*******	<0.10	2:0	<0.10	<i>2</i> 2.0	
09-Mar-2009	BOD5	.0503	0.57	.0503	0.86		NULL		7	24	7	. 36	_
06-Apr-2009	BOD5	.0144	0.57	.0144	34 1 10 N 10 N		NULL	*****	2	24	2	36	
08-May-2009	BOD5	k.0144	0.57	<.0144	0.86	KG/D	NULL	*****	<2	24	<2	36	-
05-Jun-2009	BOD5	.0261	. 0.57	.0261	0.86	KG/D	NULL	De In	3	24	3	36	М
06-Jul-2009	BOD5	.0136	0.57	.0136	0.86	KG/D		*****	<2	24	<2		_
07-Oct-2009	BOD5	.0121	0.57	.0121	0.86	KG/D		*******	. 2	24		- 36	
05-Nov-2009	BOD5	.0568	0.57	.0568	0.86	KG/D	NULL	*******	10	24	10	36	_
04-Dec-2009	BOD5	k.0114	-0.57	<.0114	0.86	KG/D		*****	<2	24	<2		
08-Jan-2010	BOD5	.0363	0.57	.0363	0.86	1	NULL	*******	6	24	6		_
04-Feb-2010	BOD5	.0424	0.57	.0424	0.86	KG/D	<u> </u>	******	7	24	7	36	М
08-Mar-2010	BOD5	.0360	0.57	.0360	. 0.86	KG/D		*****	5	24		- 36	-
09-Apr-2010	BOD5	.0965	0.57	.0965	0.86	KG/D	NULL	*****	15	~ 24	15		
10-May-2010	BOD5	0.0144	0.57	< 0.0144	0.86	KG/D	NULL	*****	<2	24	<2		
04-Jun-2010	BOD5	k.0136	0.57	<.0136	0.86	KG/D	NULL	*****	<2	24	<2	937	
07-Jul-2010	BOD5	<.0129	0.57	<.0129		KG/D	NULL		<2	. 24.	<2	7.557.54	(*
08-Oct-2010	BOD5	.0159	0.57	.0159		KG/D		*****	2			36	_
09-Nov-2010	BOD5	.0136	0.57	.0136	0.86		NULL	*******	2	24	2		
06-Dec-2010	BOD5	<.0091	0.57	<.0091	0.86	KG/D	NULL	******	<2	24	<2		
07-Jan-2011	BOD5	.0273	0.57	.0273	0.86	KG/D	NULL	*****	4	. 24	4	36	
03-Feb-2011	BOD5	.0772	0.57	.0772	regard of Control	KG/D		****	12	1 24	12	36	
07-Mar-20 11	BOD5	.0193	0.57	.0193		KG/D		*****	3	20 1.1	3	∜∴36	_
07-Apr-2011	BOD5	.0193	0.57	.0193		KG/D		*******	3	. 24	3	36	1.
04-May-2011	BOD5	.0182	0.57	.0182	0.86	1		*****	3	-24	3		-
06-Jun-2011	BOD5	<.0136	0.57	<.0136	0.86	J	NULL	*****	<2	24	<2	A	
07-Jul-2011	BOD5	.0242	0.57	.0242		KG/D	NULL	*****	4	24	4		_
03-Oct-2011	BOD5	k.0129	0.57	<.0129	W	KG/D		*****	<2	24	<2	25 25 20	<u> </u>
03-Nov-2011	BOD5	.0193		.0193	2 m	KG/D		*******	3	24	3	, , , , ,	4_
06-Dec-2011	BOD5		0.57	.0227	Free Contract Contrac	KG/D		*****	4	.24	4		٠
09-Jan-2012	BOD5			<.0114			1			24	i	- 36	
06-Feb-2012	BOD5		0.57		0.86		NULL	*****		24		36	Īм
08-Mar-2012	BOD5		0.57		. 0.86		NULL	5 4C 4		24		36	
09-Apr-2012	BOD5		0.57	.0121	0:86	<u> </u>		******	2	24		36	
03-May-2012	BOD5	.0848	31.15	.0848		KG/D	NIII			24		36 36	
10-Jun-2012	BOD5		0.57	.0606	-0.86			*****		24		36	
)5-Jul-2012	BOD5	.0477	0.57	.0477	1,2-0,3	KG/D		*****					_
03-Oct-2012	BOD5		0.57	.0363	. Professional .			****		. 24		36 36	

05-Nov-2012	BOD5	.0303 0.57	.0303 2 0.86 KG/D	NULL *******	5 24	5 36 MG/L
06-Dec-2012	BOD5	.0454 0.57	10 10 10 10 10 10 10 10 10 10 10 10 10 1	NULL	8 24	8 36 MG/L
04-Jan-2013	BOD5	.0182 0.57	.0182 086 KG/D	NULL *******	3 3 24	3 36 MG/L
08-Feb-2013	BOD5	k.0159 0.57	3. N. A. CANAL.	NULL ********	<2 24	<2 36 MG/L
05-Mar-2013	BOD5	.0129 0.57	.0129 0.86 KG/D	NULL *******	2 24	2 36 MG/L
08-Apr-2013	BOD5	.0387 0.57		NULL ******	6 24	6 ₹ 36 MG/L
08-May-2013	BOD5	.0193 0.57	4	NULL	3 2 24	3 36 MG/L
07-Jun-2013	BOD5	.0121 0.57	.0121 - 0.86 KG/D	NULL	2 24	2 36 MG/L
09-Mar-2009	PH	NULL *******	NULL NULL	6.6	NULL ******	7.0 9.0 SU
06-Apr-2009	PH	NULL *******	NULL ***********************************	6.7 6.0	NULL	7.0 9.0 SU
08-May-2009	PH	NULL	NULL MANAGE NULL	6.6	NULL ******	7.0 9.0 SU
05-Jun-2009	PH	NULL ********	NULL NULL	6.6 6.0	NULL ******	7.0 9.0 SU
06-Jul-2009	PH	NULL	NULL ******* NULL	6.7 36.0	NULL ********	7.0 9.0 SU
07-Oct-2009	PH	NULL	NULL ******** NULL	6.3 - 6.0	NULL ******	6.6 9.0 SU
05-Nov-2009	PH	NULL	NULL ******** NULL	6.4 6.0	NULL ****	6.7 9.0 SU
04-Dec-2009	PH	NULL *********	NULL ******* NULL	6.5 6.0	NULL ******	6.9 9.0 SU
08-Jan-2010	PH	NULL ********	NULL MULL	6.6 6.0	NULL ******	6.9
04-Feb-2010	PH	NULL ********	NULL NULL	6.6 6.0	NULL ******	6.9 9.0 SU
08-Mar-2010	PH	NULL ********	NULL NULL	6.6 6.0	NULL *******	6.9 9.0 SU
09-Apr-2010	PH	NULL	NULL ******** NULL	6.6 6.0	NULL ******	7.0
10-May-2010	PH	NULL ********	NULL ******** NULL	6.6 6.0	NIII ******	6.9 9.0 SU
04-Jun-2010	PH	NULL	NULL ******* NULL	6.6 6.0	NULL *****	7.0 9.0 SU
07-Jul-2010	PH	NULL	NULL NULL	6.6	NULL ******	7.0 9.0 SU
08-Oct-2010	PH	NULL	NULL ******** NULL	6.5 6.0	NULL *******	6.7 9.0 SU
09-Nov-2010	PH	NULL ***********************************	NULL MULL	6.6	NULL *******	6.9 9 0 SU
06-Dec-2010	PH	NULL *******	NULL ******** NULL	6.6 6.0	NULL	6.9 9.0 SU
07-Jan-2011	PH	NULL *******	NULL NULL	6.6 60	NULL	6.9 90 SU
03-Feb-2011	PH	NULL *******	NULL NULL	6.6 6.0	NULL *******	6.9
07-Mar-2011	PH	NULL	NULL	6.6 6.0	NULL ****	6.9 2 9 0 SU
07-Apr-2011	PH	NULL	NULL NULL	6.6 6.0	NULL *******	6.9 90 SU
04-May-2011	PH	NULL	NULL NULL	6.6 6.0	NULL *******	7.0 9.0 SU
06-Jun-2011	PH	NULL *******	NULL NULL	6.6 6.0	NULL ******	6.9 9.0 SU
07-Jul-2011	PH	NULL *******	NULL NULL	6.6 6.0	NULL ******	6.9 3.9.0 SU
03-Oct-2011	РН	NULL ****	NULL ******** NULL	6.6 6.0	NULL *******	6.9 9.0 SU
03-Nov-2011	РН	NULL *********	NULL	6.6 6.0	NULL ******	6.9 3.0 SU
06-Dec-2011	PH	NULL ******	NULL NULL	6.6 2 6.0	NULL *******	6.9 9:0 SU
09-Jan-2012	РН	NULL *********	200134312171	6.6	NULL *******	6.9 9.0 SU
06-Feb-2012	РН	NULL	NULL NULL	6.6	NULL ****	6.9 9.0 SU
08-Mar-2012	РН	NULL *******	NULL NULL	6.6	NULL ******	6.9 9.0 SU
09-Apr-2012	PH	NULL ****		6.6 \$6.0	NULL NULL	6.9 9.0 SU
3-May-2012	PH	NULL *******		6.6	All II I management	7.0 9.0 SU
10-Jun-2012	РН	NULL	NULL NULL	6.6 6.0	NULL ********	6.9 9.0 SU
)5-Jul-2012	PH	NULL	NULL NULL	6.6	NULL MACE	6.9 9.0 SU

03-Oct-2012	PH	NULL ****	**** NULL	**************************************	6.6 6.0	NULL ******	6.9 9.0 SU
05-Nov-2012	PH	NULL *****	·	******** NULL	6.6 6.0	NULL ******	7.0
06-Dec-2012	PH	NULL	ς .	**************************************	6.5 6.0	NULL ******	7.0 9.0 SU
04-Jan-2013	РН	NULL *****		********* NULL	6.4 6.0	NULL ******	6.7 9.0 SU
08-Feb-2013	PH	NULL		******** NULL	6.7 6.0	NULL *******	7.0 9.0 SU
05-Mar-2013	PH	NULL	-4	NULL	6.8 6.0	NULL ******	7.2 9.0 SU
08-Apr-2013	PH	NULL	- 2	**************************************	6.6 6.0	NULL *******	7.0 9.0 SU
08-May-2013	РН	NULL	.24	**************************************	6.4 6.0	NULL *******	6.9 9.0 SU
07-Jun-2013	РН	NULL		NULL	6.2 6.0	NULL ******	6.9 9.0 SU
				727	15 72 335 25		
			168 - 158		9	0th percentile:	7.0
			8- 2 ⁷ 8 -9 ₂₀ -58- 2		1	0th percentile	6.6
09-Mar-2009	TSS	<.0072	57 <.0072	0.86 KG/D	NULL ********	<1.00 24	<1.00 36 MG/L
06-Apr-2009	TSS	.0072	57 .0072	. 0.86 KG/D	NULL ****	<1.00 24	<1.00 36 MG/L
08-May-2009	TSS	k.0072 0	57 <.0072	- 0.86 KG/D	NULL *******	<1.00 ** *24	<1.00 4 36 MG/L
05-Jun-2009	TSS	.0200	57 .0200	0.86 KG/D	NULL ********	2.30 24	2.30 36 MG/L
06-Jul-2009	TSS	.0164	.57 .0164	0.86 KG/D	NULL *******	2.40 24	2.40 36 MG/L
07-Oct-2009	TSS	.0340 0	.57 .0340	0.86 KG/D	NULL *******	5.60 24	5.60 36 MG/L
05-Nov-2009	TSS	.0329	.57 .0329	0.86 KG/D	NULL ******	5.80 24	5.80 🛫 36 MG/L
04-Dec-2009	TSS	.0148	.57 .0148	0.86 KG/D	NULL *******	2.60 24	2.60 36 MG/L
08-Jan-2010	TSS	.0097	57 .0097	0.86, KG/D	NULL *******	1.60 24	1.60 36 MG/L
04-Feb-2010	TSS	.0067	57, .0067	0.86 KG/D	NULL	1.10 24	1.10 36 MG/L
08-Mar-2010	TSS	.0187	.57 .0187	0.86 KG/D	NULL *******	2.60 24	2.60 36 MG/L
09-Apr-2010	TSS	.0154	.57 .0154	0.86 KG/D	NULL *******	2.40 24	2.40 36 MG/L
10-May-2010	TSS	0.0072	.57 <0.0072	<i></i>	NULL ********	<1.00 : 4 24	<1.00 36 MG/L
04-Jun-2010	TSS	<.0068 ⊘ 0	57 <.0068	- 0.86 KG/D	NULL *******	<1.00 24	<1.00 36 MG/L
07-Jul-2010	TSS	<.0064 0	.57 <.0064	0.86 KG/D	NULL	<1.00 24	<1.00 36 MG/L
08-Oct-2010	TSS	.0119 0	.57 .0119	0.86; KG/D	NULL *******	1.50 24	1.50 36 MG/L
09-Nov-2010	TSS	.0170 0	.57 .0170	0.86 KG/D	NULL	2.50 24	2.50 36 MG/L
06-Dec-2010	TSS	.0045	57 .0045	0.86 KG/D	NULL ****	1.00 24	1.00 36 MG/L
07-Jan-2011	TSS	.0068	.57 .0068	0.86 KG/D	NULL ******	<1.00 24	<1.00 36 MG/L
03-Feb-2011	TSS	.0431 👯 0	57 .0431	0.86 KG/D	NULL *******	6.70 24	6.70 4 36 MG/L
07-Mar-2011	TSS	.0386 0	.57 .0386	. 0.86 KG/D	NULL (***)	6.00 24	6.00 36 MG/L
07-Apr-2011	TSS	.0109 5.0	.57 .0109	0.86 KG/D	NULL MARKET	1.70 24	1.70 36 MG/L
04-May-2011	TSS	.0206 O	.57 .0206	0,86 KG/D	NULL *******	3.40 24	3.40 💥 36 MG/L
06-Jun-20 1 1	TSS	.0085	.57; .0085	%, 0.86 KG/D	NULL ********	1.40 24	1.40 36 MG/L
07-Jul-2011	TSS	.0091	.57 .0091	0.86 KG/D	NULL ********	1.50 24	1.50 36 MG/L
03-Oct-2011	TSS	.0103	.57 .0103	0.86 KG/D	NULL ********	1.6024	1.60 3 36 MG/L
03-Nov-2011	TSS	<.0064	57 <.0064	0.86 KG/D	NULL *******	<1.00 24	<1.00 36 MG/L
06-Dec-2011	TSS	.0204 0	57, .0204	0.86 KG/D	NULL ********	3.60 24	3.60 36 MG/L
09-Jan-2012	TSS	<.0057 👵 0	57 <.0057	0:86 KG/D	NULL *******	<1.00 24	<1.00 36 MG/L
06-Feb-2012	TSS	<.0057 \}_0	57 <.0057	0.86 KG/D	NULL ******	<1.00 24	<1.00 36 MG/L

08-Mar-2012	TSS	.0079	1:0.57	.0079	0.86	KG/D	NULL	12 pg. 22 12	1.30	. 24	1.30	-36	MG/L
09-Apr-2012	TSS		0.57	.0157	°0.86			*******		24	2.60	₹ 36	MG/L
03-May-2012	TSS	.0454	0.57	.0454	0.86	KG/D		*****	7.50	.24	7.50	3,36	MG/L
10-Jun-2012	TSS	.0248	0.57	.0248	0.86	KG/D	NULL	******	4.10	24	4.10	36	MG/L
05-Jul-2012	TSS	.0673	.0.57	.0673	0.86	KG/D		*****	12.7	. 24	12.7	36	MG/L
03-Oct-2012	TSS	.0539	0:57	.0539	0.86	KG/D	NULL	*****	8.90	^ 24	8.90	36	MG/L
05-Nov-2012	TSS	.0696	0.57	.0696	0.86	KG/D		*****	11.5	24	11.5	36	MG/L
06-Dec-2012	TSS	.1016	0.57	.1016	-0.86	KG/D	NULL	- 143 - 143		24	17.9		MG/L
04-Jan-2013	TSS	.0472	0.57	.0472	₩.0.86	KG/D		****	7.8		7.8	∹,36	MG/L
08-Feb-2013	TSS	.0159	0.57	.0159	0.86	KG/D		*****	2.00	1- 24	2.00	:- 36·	MG/L
05-Mar-2013	TSS	.0064	0.57	.0064	0.86	KG/D		**********	1	, 24	1		MG/L
08-Apr-2013	TSS	.0245	0.57	.0245	0.86	KG/D			3.80	24	3.80		MG/L
08-May-2013	TSS	.0830	0.57	.0830	0.86	KG/D		********		24	12.9		
07-Jun-2013	TSS	.1096	0.57	.1096	∞0.86	KG/D		*******		. 24	18.1		

JUCKETTS ELEMENTARY OL TOTAL AMMONIA EFFLUENT LI CION CALCULATIONS

Calculation for Total Ammonia values at different pH and Temperature than listed in the Water Quality Standards (VR680-21-01.14B)

Temperature = 26°C

THE ONE HOUR AVERAGE CONCENTRATION OF AMMONIA (IN MG/L AS UN-IONIZED NH_3) CAN BE CALCULATED BY USING THE FOLLOWING FORMULAS.

Acute criteria concentration = 0.52/FT/FPH/2

where: FT = Final Temperature

 $FT = 10^{0.03(20 - TCAP)}$; $TCAP < T < 30^{\circ}C$

TCAP = 25°C; when trout and other sensitive coldwater species are absent

 $FT = 10^{0.03(20-25)}$

 $FT = 10^{0.03(-5)}$

 $FT = 10^{-0.15} = 0.71$

where: FPH = Final pH

$$FPH = \frac{(1 + 10^{7.4} - pH)}{1.25}$$
; 6.5 < pH < 8.0

FPH = 2.8

Therefore: ACUTE CRITERIA CONCENTRATION = 0.52/0.71/2.8/2 = .13

CONVERSION FROM UN-IONIZED TO TOTAL AMMONIA CAN BE CALCULATED BY USING THE FOLLOWING FORMULAS.

TOTAL AMMONIA CRITERIA = CALCULATED UN-IONIZED AMMONIA CRITERIA DIVIDED BY FRACTION OF UN-IONIZED AMMONIA

Where: Fraction of un-ionized ammonia = $1/(10^{pKa-pH} + 1)$

where: pKa = 0.09018 + (2729.92/(273.2 + temperature °C))

pKa = 9.21

Fraction of un-ionized ammonia = $1/(10^{9.21 - 7.0} + 1)$

= 0.006

THEREFORE: TOTAL ACUTE AMMONIA CRITERIA = CALCULATED UN-IONIZED AMMONIA CRITERIA DIVIDED BY FRACTION OF UN-IONIZED AMMONIA

TOTAL ACUTE AMMONIA CRITERIA = 0.13/0.006 = 21.6 mg/l

ZING nglex . 824= 17.8 mg/e Ammonia As N

Calculation for Total Ammonia values at different pH and Temperature than listed in the Water Quality Standards (VR680-21-01.14B)

Temperature = 26°C

THE 4-DAY AVERAGE CONCENTRATION OF AMMONIA (IN MG/L AS UN-IONIZED NH₃) CAN BE CALCULATED BY USING THE FOLLOWING FORMULAS.

Chronic criteria concentration = 0.8/FT/FPH/RATIO

where: FT = Final Temperature

 $FT = 10^{0.03(20 - TCAP)}$; $TCAP < T < 30^{\circ}C$

TCAP = 20°C; when trout and other sensitive coldwater species are absent

$$FT = 10^{0.03(20-20)}$$

$$FT = 10^{\circ} = 1$$

where: FPH = Final pH

$$FPH = \frac{(1 + 10^{7.4} - pH)}{1.25}$$
; 6.5 < pH < 8.0

FPH = 2.8

RATIO =
$$\frac{20.25 \times (10^{7.7-pH})}{(1+10^{7.4-pH})}$$
; 6.5 < pH< 7.7

RATIO = 28.9

Therefore: CHRONIC CRITERIA CONCENTRATION = 0.8/1/2.8/28.9 = 0.0099

CONVERSION FROM UN-IONIZED TO TOTAL AMMONIA CAN BE CALCULATED BY USING THE FOLLOWING FORMULAS.

TOTAL CHRONIC AMMONIA CRITERIA = CALCULATED UN-IONIZED AMMONIA CRITERIA DIVIDED BY FRACTION OF UN-IONIZED AMMONIA

Where: Fraction of un-ionized ammonia = $1/(10^{pKe-pH} + 1)$

where: pKa = 0.09018 + (2729.92/(273.2 + temperature °C))
pKa = 9.21

Fraction of un-ionized ammonia = $1/(10^{9.21} - 7.0 + 1)$

= 0.006

THEREFORE: TOTAL CHRONIC AMMONIA CRITERIA = CALCULATED UN-IONIZED AMMONIA CRITERIA
DIVIDED BY FRACTION OF UN-IONIZED
AMMONIA

TOTAL CHRONIC AMMONIA CRITERIA = 0.0099/0.006 = 1.65 mg/l

Analysis of the Lucketts ES effluent day or ammonia

The statistics for ammonfa are:

Number of values = 1
Quantification level = .2
Number _ quantification = 0
Expected value = 10

Varience = 36.00001

C.V. = .6

97th percentile = 24.33418

Statistics used = Reasonable potential assumptions - Type 2 data

The WLAS for ammonia are:

Acute WLA = 17.8 Chronic WLA = 1.4 Human Health WLA = ---

The limits are based on chronic toxicity and 1 samples/month.

Maximum daily limit = 2.047605 Average monthly limit = 2.047605

DATA

10

6/13/2013 11:34:37 AM

Facility = Lucketts Elementary
Chemical = Chlorine
Chronic averaging period = 4
WLAa = 0.019
WLAc = 0.011
Q.L. = 0.1
samples/mo. = 28
samples/wk. = 7

Summary of Statistics:

observations = 1

Expected Value = .2

Variance = .0144

C.V. = 0.6

97th percentile daily values = .486683

97th percentile 4 day average = .332758

97th percentile 30 day average = .241210

< Q.L. = 0

Model used = BPJ Assumptions, type 2 data

A limit is needed based on Chronic Toxicity
Maximum Daily Limit = 1.60883226245855E-02
Average Weekly limit = 9.8252545713861E-03
Average Monthly LImit = 8.02152773888032E-03

The data are:

0.2

Public Notice - Environmental Permit

PURPOSE OF NOTICE: To seek public comment on a draft permit from the Department of Environmental Quality that will allow the release of treated wastewater into a water body in Loudoun County, Virginia.

PUBLIC COMMENT PERIOD: July 18, 2013 to August 16, 2013

PERMIT NAME: Virginia Pollutant Discharge Elimination System Permit – Wastewater issued by DEQ, under the authority of the State Water Control Board

APPLICANT NAME, ADDRESS AND PERMIT NUMBER:

Loudoun County Public Schools

21000 Education Court, Ashburn, VA 20148

VA0021750

NAME AND ADDRESS OF FACILITY:

Lucketts Elementary School

14550 James Madison Highway, Leesburg, VA 20176

PROJECT DESCRIPTION: Loudoun County Public Schools has applied for a reissuance of a permit for the public Lucketts Elementary School. The applicant proposes to release treated sewage wastewaters from an elementary school, community center and volunteer fire station at a rate of 0.0063 million gallons per day into a water body. This permit reissuance also includes an expanded rate of 0.01175 million gallons per day. Domestic sludge is not generated at this facility. The facility proposes to release the treated sewage in the Limestone Branch, UT, in Loudoun County, Virginia in the Potomac River watershed. A watershed is the land area drained by a river and its incoming streams. The permit will limit the following pollutants to amounts that protect water quality: pH, biochemical oxygen demand, total suspended solids, dissolved oxygen, ammonia as N, E. coli and total residual chlorine.

HOW TO COMMENT AND/OR REQUEST A PUBLIC HEARING: DEQ accepts comments and requests for public hearing by hand-delivery, e-mail, fax or postal mail. All comments and requests must be in writing and be received by DEQ during the comment period. Submittals must include the names, mailing addresses and telephone numbers of the commenter/requester and of all persons represented by the commenter/requester. A request for public hearing must also include: 1) The reason why a public hearing is requested. 2) A brief, informal statement regarding the nature and extent of the interest of the requester or of those represented by the requester, including how and to what extent such interest would be directly and adversely affected by the permit. 3) Specific references, where possible, to terms and conditions of the permit with suggested revisions. A public hearing may be held, including another comment period, if public response is significant, based on individual requests for a public hearing, and there are substantial, disputed issues relevant to the permit.

CONTACT FOR PUBLIC COMMENTS, DOCUMENT REQUESTS AND ADDITIONAL INFORMATION: The public may review the draft permit and application at the DEQ-Northern Regional Office by appointment, or may request electronic copies of the draft permit and fact sheet.

Name: Douglas Frasier